

INDUSTRIAL COMPONENT DATA

US 7 300 FT 6340377 OBO BETTERMANN U support 3-sided perforated, 70x50x3000, Hot-dip galvanised, DIN EN ISO ..

Brand: OBO BETTERMANN | Manufacturer Part Number: US 7 300 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	US 7 300 FT
Catalog number	6340377
Category	Mounting rail/-profile
Minimum order	1 Pcs
Document ID	EO-2547055005
Generated	2026-07-31

Product Overview

U support 3-sided perforated, 70x50x3000, Hot-dip galvanised, DIN EN ISO 1461, Steel, St
US 7 support FT. U support in fixed lengths. Dimensions 70 x 50 mm.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > mounting accessories

Additional Product Information

Breakable no
CO2 Footprint (GWP) Cradle-to-Gate 27,9628 kg CO2e / 1 Piece
Colour zinc
Dimension 70x50x3000
Dimension 70 x 50 x 4
Dimension L 3000 mm
Height 50 mm
Hole width 14 mm
Length 3000 mm
Maintain electrical functions no
Material Steel
Material thickness 4 mm
Profile shape U profile
Slot width 62 mm

Static value A 4,59 cm²
Static value I_y 13,79 cm⁴
Static value I_z 36,84 cm⁴
Static value W_y 4,11 cm³
Static value W_z 10,53 cm³
Surface Hot-dip galvanised
Type of perforation 3 sides perforated
Version for Single profile
Width 70 mm
With tothing no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / US 7 300 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.