

INDUSTRIAL COMPONENT DATA

DBV 60 400 F DD 7131644 OBO BETTERMANN Cover for 90° vertical bend falling, B400mm, Zinc-aluminium coated, d..

Brand: OBO BETTERMANN | Manufacturer Part Number: DBV 60 400 F DD



Manufacturer	OBO BETTERMANN
MPN / Reference	DBV 60 400 F DD
Catalog number	7131644
Category	Bend cover for cable support system
Minimum order	1 Pcs
Document ID	EO-3D85C87F3D
Generated	2026-08-03

Product Overview

Cover for 90° vertical bend falling, B400mm, Zinc-aluminium coated, double-dip, Steel, St
Cover for 90° vertical bend, falling, DD. Cover for falling vertical bends of side height 60 mm.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Tapas
--------------	---

Additional Product Information

Bend (angle) 90°
Change of direction Vertical, falling
CO2 Footprint (GWP) Cradle-to-Gate 5,5053 kg CO2e / 1 Piece
Colour zinc
Dimension B400mm
Dimension B 400 mm
Fastening type Sash lock
Height 60 mm
Hinged no
Maintain electrical functions no
Material Steel
Plate thickness 0,03 in
Plate thickness 0,75 mm
Rustproof steel, pickled no

Suitable for cable ladder no

Suitable for cable tray yes

Suitable for mesh cable tray no

Surface Strip galvanised zinc/aluminium, Double Dip

Width 16 in

Width 400 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / DBV 60 400 F DD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.