

INDUSTRIAL COMPONENT DATA

RKSM 610 A2 6047613 OBO BETTERMANN Cable tray RKSM Magic, quick connector, 60x100x3050, Stainless steel, gra..

Brand: OBO BETTERMANN | Manufacturer Part Number: RKSM 610 A2



Manufacturer	OBO BETTERMANN
MPN / Reference	RKSM 610 A2
Catalog number	6047613
Category	Cable tray/wide span cable tray
Minimum order	3 m.
Document ID	EO-4E0DB8E74B
Generated	2026-08-01

Product Overview

Cable tray RKSM Magic, quick connector, 60x100x3050, Stainless steel, grade 304, VA, 1.4301

RKSM RKSM 610 A2,Magic cable tray, with quick connector 60x100x3050 Stainless steel 1.4301, A2, 1.4301,Polished, with subsequent treatment

RKS-Magic® 60 A2 cable tray. Cable tray with integrated quick fixing system. The usable length of the cable tray is 3,000 mm.La cable tray has a continuous side perforation of 7 x 20 mm for the installation of additional joining and mounting components. The hole for the direct threaded rod suspension has a diameter of 11 mm. Magnetic insulation without cap 20 dB, with cap 50 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN**

Additional Product Information

Magnetic shield insulation without cover 20 dB, with cover 50 dB.

ETIM for 6047613 Cable tray, ladder and wire basket systems (EC000047)

Feature Name

Feature Value

Height (EF000040)

60 mm

Width (EF000008)

100 mm

Material thickness (EF000386)

0.75 mm
Length (EF001438)
3050 mm
Working length (EF006318)
3000 mm
Useful cross section (EF005140)
5800 mm²
With cover (EF007965)
No
Side perforation (EF001122)
Yes
Bottom perforation (EF004545)
Yes
NATO-mounting holes (EF006059)
No
Model (EF000010)
Integrated coupler
Type of connector (EF000141)
Click in
Suitable for circuit integrity (EF007806)
Yes
Material (EF002169)
Stainless steel
Material quality (EF001257)
Stainless steel 304
Surface protection (EF000139)
Untreated
Weight (EF000167)
1.45 kg/m
Load test type according to IEC 61537 (EF015362)
Type II
Possible support spacing (EF017261)
1 m
Safe working load according to IEC 61537 with support spacing 1.0 m (EF017263)
1200
Safe working load according to IEC 61537 with support spacing 1.5 m (EF017264)
900
Safe working load according to IEC 61537 with support spacing 2.0 m (EF017265)
600
Safe working load according to IEC 61537 with support spacing 2.5 m (EF017266)
400

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / RKSM 610 A2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.