

INDUSTRIAL COMPONENT DATA

RKSM 620 FSK RW 6048255 OBO BETTERMANN Cable tray RKSM Magic, quick connector, 60x200x3050, Pure white, 9010..

Brand: OBO BETTERMANN | Manufacturer Part Number: RKSM 620 FSK RW



Manufacturer	OBO BETTERMANN
MPN / Reference	RKSM 620 FSK RW
Catalog number	6048255
Category	Cable tray/wide span cable tray
Minimum order	100 Pcs
Document ID	EO-FA5DB8C4FC
Generated	2026-08-05

Product Overview

Cable tray RKSM Magic, quick connector, 60x200x3050, Pure white, 9010, Strip galvanised/powder-coated, DIN EN 10147, Steel, St

Cable tray RKS-Magic® 60, pure white. Cable tray with integrated quick fastening system. Continuous side perforations of 7 x 20 mm for the installation of additional connection and mounting components. With 11 mm perforation in the base for direct threaded rod suspension. Usable length 3,000 mm. Magnetic shield insulation without cover 20 dB, with cover 50 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN
--------------	---

Additional Product Information

Base perforation 1

CO2 Footprint (GWP) Cradle-to-Gate 4,5163 kg CO2e / 1 Meter

Colour Pure white; RAL 9010

Connector version Integrated connector

Dimension 60x200x3050

Dimension B 200 mm

Dimension x 100 mm

Dimension y 150 mm

Fire protection Maintenance of electrical function of cable-specific support structure

Height 60 mm
Length 3050 mm
Load test type according to IEC 61537 Type II
Maintain electrical functions yes
Material Steel
Mounting perforation in base yes
NATO hole pattern no
NEMA load class 8AA
Plate thickness 0,75 mm
Rustproof steel, pickled no
Side perforation yes
Support spacing 1.0 m 1,2 kN/m
Support spacing 1.5 m 0,9 kN/m
Support spacing 2.0 m 0,6 kN/m
Support spacing 2.5 m 0,4 kN/m
Surface PES50 - Polyester/epoxy/visual surface coated
Type of connector, cable support system Click fastening
Usable cross-section 11800 mm²
Usable cross-section 118 cm²
Usable length 3000 mm
Wide-span version no
Width 200 mm
With cover no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / RKSM 620 FSK RW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.