

INDUSTRIAL COMPONENT DATA

RKSM 620 A2 6047640 OBO BETTERMANN Cable tray RKSM Magic, quick connector, 60x200x3050, Stainless steel, gra..

Brand: OBO BETTERMANN | Manufacturer Part Number: RKSM 620 A2



Manufacturer	OBO BETTERMANN
MPN / Reference	RKSM 620 A2
Catalog number	6047640
Category	Cable tray/wide span cable tray
Minimum order	3 m.
Document ID	EO-DB39064A0F
Generated	2026-08-04

Product Overview

Cable tray RKSM Magic, quick connector, 60x200x3050, Stainless steel, grade 304, VA, 1.4301

RKSM RKSM 620 A2, Magic cable tray, with quick connector 60x200x3050 Stainless steel 1.4301, A2, 1.4301, Polished, with subsequent treatment

Cable tray RKS-Magic® 60 A2. Cable tray with integrated quick fastening system. The usable length of the cable tray is 3,000 mm. The cable tray has continuous side perforations of 7 x 20 mm for the installation of additional connection and mounting components. The perforation for direct threaded rod suspension has a diameter of 11 mm. Magnetic shield insulation without cover 20 dB, with cover 50 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN
--------------	---

Additional Product Information

Base perforation 1

CO2 Footprint (GWP) Cradle-to-Gate 10,5828 kg CO2e / 1 Meter

Colour stainless steel

Connector version Integrated connector

Dimension 60x200x3050

Dimension B 200 mm

Dimension x 100 mm

Dimension y 150 mm

Fire protection Maintenance of electrical function of cable-specific support structure

Height 60 mm
Length 3050 mm
Load test type according to IEC 61537 Type II
Magnetic shield insulation with cover 50 dB
Magnetic shield insulation without cover 20 dB
Maintain electrical functions yes
Material Stainless steel 1.4301
Mounting perforation in base yes
NATO hole pattern no
Plate thickness 0,75 mm
Rustproof steel, pickled no
Side perforation yes
Support spacing 1.0 m 1,2 kN/m
Support spacing 1.5 m 0,9 kN/m
Support spacing 2.0 m 0,6 kN/m
Support spacing 2.5 m 0,4 kN/m
Surface Bright, treated
Type of connector, cable support system Click fastening
Usable cross-section 118 cm²
Usable cross-section 11800 mm²
Usable length 3000 mm
Wide-span version no
Width 200 mm
With cover no
ETIM for 6047640 Cable tray, ladder and wire basket systems (EC000047)
Feature Name
Feature Value
Height (EF000040)
60 mm
Width (EF000008)
200 mm
Material thickness (EF000386)
0.75 mm
Length (EF001438)
3050 mm
Working length (EF006318)
3000 mm
Useful cross section (EF005140)
11800 mm²
With cover (EF007965)
No
Side perforation (EF001122)
Yes
Bottom perforation (EF004545)
Yes
NATO-mounting holes (EF006059)
No

Model (EF000010)
Integrated coupler
Type of connector (EF000141)
Click in
Suitable for c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / RKSM 620 A2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.