


INDUSTRIAL COMPONENT DATA

RKSM 630 FSK RW 6048257 OBO BETTERMANN Cable tray RKSM Magic, quick connector, 60x300x3050, Pure white, 9010..

Brand: OBO BETTERMANN | Manufacturer Part Number: RKSM 630 FSK RW



Manufacturer	OBO BETTERMANN
MPN / Reference	RKSM 630 FSK RW
Catalog number	6048257
Category	Cable tray/wide span cable tray
Minimum order	100 Pcs
Document ID	EO-62B1AD0A84
Generated	2026-08-03

Product Overview

Cable tray RKSM Magic, quick connector, 60x300x3050, Pure white, 9010, Strip galvanised/powder-coated, DIN EN 10147, Steel, St

Cable tray RKS-Magic® 60, pure white. Cable tray with integrated quick fastening system. Continuous side perforations of 7 x 20 mm for the installation of additional connection and mounting components. With 11 mm perforation in the base for direct threaded rod suspension. Usable length 3,000 mm. Magnetic shield insulation without cover 20 dB, with cover 50 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN
--------------	---

Additional Product Information

Base perforation 1

CO2 Footprint (GWP) Cradle-to-Gate 5,8395 kg CO2e / 1 Meter

Colour Pure white; RAL 9010

Connector version Integrated connector

Dimension 60x300x3050

Dimension B 300 mm

Dimension t 300 mm

Dimension x 200 mm

Dimension y 250 mm

Fire protection Maintenance of electrical function of cable-specific support structure

Height 60 mm

Length 3050 mm

Load test type according to IEC 61537 Type II

Maintain electrical functions yes

Material Steel

Mounting perforation in base yes

NATO hole pattern no

NEMA load class 8AA

Plate thickness 0,75 mm

Rustproof steel, pickled no

Side perforation yes

Support spacing 1.0 m 1,2 kN/m

Support spacing 1.5 m 0,9 kN/m

Support spacing 2.0 m 0,6 kN/m

Support spacing 2.5 m 0,4 kN/m

Surface PES50 - Polyester/epoxy/visual surface coated

Type of connector, cable support system Click fastening

Usable cross-section 178 cm²

Usable cross-section 17800 mm²

Usable length 3000 mm

Wide-span version no

Width 300 mm

With cover no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / RKSM 630 FSK RW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.