

INDUSTRIAL COMPONENT DATA

RKSM 630 A2 6047656 OBO BETTERMANN Cable tray RKSM Magic, quick connector, 60x300x3050, Stainless steel, gra..

Brand: OBO BETTERMANN | Manufacturer Part Number: RKSM 630 A2



Manufacturer	OBO BETTERMANN
MPN / Reference	RKSM 630 A2
Catalog number	6047656
Category	Cable tray/wide span cable tray
Minimum order	3 m.
Document ID	EO-E4988F3EED
Generated	2026-08-01

Product Overview

Cable tray RKSM Magic, quick connector, 60x300x3050, Stainless steel, grade 304, VA, 1.4301

RKSM RKSM 630 A2,Magic cable tray, with quick connector 60x300x3050 Stainless steel 1.4301, A2, 1.4301,Polished, with subsequent treatment

Cable tray RKS-Magic® 60 A2. Cable tray with integrated quick fastening system. The usable length of the cable tray is 3,000 mm.The cable tray has continuous side perforations of 7 x 20 mm for the installation of additional connection and mounting components.The perforation for direct threaded rod suspension has a diameter of 11 mm.Magnetic shield insulation without cover 20 dB, with cover 50 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN**

Additional Product Information

Base perforation 1

CO2 Footprint (GWP) Cradle-to-Gate 13,6398 kg CO2e / 1 Meter

Colour stainless steel

Connector version Integrated connector

Dimension 60x300x3050

Dimension B 300 mm

Dimension t 100 mm

Dimension x 200 mm

Dimension y 250 mm

Fire protection Maintenance of electrical function of cable-specific support structure

Height 60 mm

Length 3050 mm

Load test type according to IEC 61537 Type II

Magnetic shield insulation with cover 50 dB

Magnetic shield insulation without cover 20 dB

Maintain electrical functions yes

Material Stainless steel 1.4301

Mounting perforation in base yes

NATO hole pattern no

Plate thickness 0,75 mm

Rustproof steel, pickled no

Side perforation yes

Support spacing 1.0 m 1,2 kN/m

Support spacing 1.5 m 0,9 kN/m

Support spacing 2.0 m 0,6 kN/m

Support spacing 2.5 m 0,4 kN/m

Surface Bright, treated

Type of connector, cable support system Click fastening

Usable cross-section 178 cm²

Usable cross-section 17800 mm²

Usable length 3000 mm

Wide-span version no

Width 300 mm

With cover no

ETIM for 6047656 Cable tray, ladder and wire basket systems (EC000047)

Feature Name

Feature Value

Height (EF000040)

60 mm

Width (EF000008)

300 mm

Material thickness (EF000386)

0.75 mm

Length (EF001438)

3050 mm

Working length (EF006318)

3000 mm

Useful cross section (EF005140)

17800 mm²

With cover (EF007965)

No

Side perforation (EF001122)

Yes

Bottom perforation (EF004545)

Yes

NATO-mounting holes (EF006059)

No

Model (EF000010)

Integrated coupler

Type of connector (EF000141)

Clic...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / RKSM 630 A2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.