

INDUSTRIAL COMPONENT DATA

RKSM 640 VA4571 6047692 OBO BETTERMANN Cable tray RKSM Magic, quick connector, 60x400x3050, Stainless steel,...

Brand: OBO BETTERMANN | Manufacturer Part Number: RKSM 640 A4



Manufacturer	OBO BETTERMANN
MPN / Reference	RKSM 640 A4
Catalog number	6047692
Category	Cable tray/wide span cable tray
Minimum order	3 m.
Document ID	EO-DB3F068B79
Generated	2026-08-04

Product Overview

Cable tray RKSM Magic, quick connector, 60x400x3050, Stainless steel, grade 316 Ti, VA, 1.4571

Cable tray RKS-Magic® 60 A4. Cable tray with integrated quick fastening system. The usable length of the cable tray is 3,000 mm. The cable tray has continuous side perforations of 7 x 20 mm for the installation of additional connection and mounting components. The perforation for direct threaded rod suspension has a diameter of 11 mm. Magnetic shield insulation without cover 20 dB, with cover 50 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN

Additional Product Information

Base perforation 1
 CO2 Footprint (GWP) Cradle-to-Gate 18,784 kg CO2e / 1 Meter
 Colour stainless steel
 Connector version Integrated connector
 Dimension 60x400x3050
 Dimension B 400 mm
 Dimension t 200 mm
 Dimension x 300 mm
 Dimension y 350 mm
 Height 60 mm
 Length 3050 mm

Load test type according to IEC 61537 Type II
Magnetic shield insulation with cover 50 dB
Magnetic shield insulation without cover 20 dB
Maintain electrical functions no
Material Stainless steel 1.4571
Mounting perforation in base yes
NATO hole pattern no
Plate thickness 0,9 mm
Rustproof steel, pickled no
Side perforation yes
Support spacing 1.0 m 2,1 kN/m
Support spacing 1.5 m 1,35 kN/m
Support spacing 2.0 m 0,9 kN/m
Support spacing 2.5 m 0,6 kN/m
Surface Bright, treated
Type of connector, cable support system Click fastening
Usable cross-section 23800 mm²
Usable cross-section 238 cm²
Usable length 3000 mm
Wide-span version no
Width 400 mm
With cover no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / RKSM 640 A4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.