


**INDUSTRIAL COMPONENT DATA**

# WKLG 1140 FS 6311016 OBO BETTERMANN Wide clamping cable conductor with side perforation, 110x400x6000, Strip..

Brand: OBO BETTERMANN | Manufacturer Part Number: WKLG 1140 FS



|                 |                                     |
|-----------------|-------------------------------------|
| Manufacturer    | OBO BETTERMANN                      |
| MPN / Reference | WKLG 1140 FS                        |
| Catalog number  | 6311016                             |
| Category        | Cable ladder/wide span cable ladder |
| Minimum order   | 6 m.                                |
| Document ID     | EO-1CBA362276                       |
| Generated       | 2026-07-29                          |

## Product Overview

Wide clamping cable conductor with side perforation, 110x400x6000, Strip-galvanised, DIN EN 10147, Steel, St  
Wide span cable ladder WKLG 110 FS. Wide span cable ladder with perforated side rails of side height of 110 mm.  
Fastening of cables with clamp clip, type 2056.Magnetic shield insulation without cover 10 dB, with cover 15 dB.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Tray wide span**

## Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 14,7278 kg CO2e / 1 Meter

Colour zinc

Dimension 110x400x6000

Dimension 110 x 400

Dimension B 400 mm

Dimension L 6000 mm

Fastening of rung Fully riveted

Height 110 mm

Length 6000 mm

Maintain electrical functions no

Material Steel

Rail thickness 2 mm

Rung slot dimension 17,00

Rustproof steel, pickled no  
Side perforation yes  
Side rail version Profile (open)  
Support spacing 3.0 m 2,9 kN/m  
Support spacing 3.5 m 2,48 kN/m  
Support spacing 4.0 m 2,1 kN/m  
Support spacing 4.5 m 1,78 kN/m  
Support spacing 5.0 m 1,5 kN/m  
Support spacing 6.0 m 1 kN/m  
Support spacing 7.0 m 0,7 kN/m  
Surface Strip galvanized  
Usable cross-section 376 cm<sup>2</sup>  
Usable cross-section 37600 mm<sup>2</sup>  
Version of the rungs Profile perforated  
Wide-span version yes  
Width 400 mm

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / WKLG 1140 FS with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.