


INDUSTRIAL COMPONENT DATA

WKLG 1150 FT 6311071 OBO BETTERMANN Wide clamping cable conductor perforated side rail, 110x500x6000, Hot-di..

Brand: OBO BETTERMANN | Manufacturer Part Number: WKLG 1150 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	WKLG 1150 FT
Catalog number	6311071
Category	Cable ladder/wide span cable ladder
Minimum order	6 m.
Document ID	EO-072D116BB1
Generated	2026-08-03

Product Overview

Wide clamping cable conductor perforated side rail, 110x500x6000, Hot-dip galvanised, DIN EN ISO 1461, Steel, St
Wide span cable ladder WKLG 110 FT. Wide span cable ladder with perforated side rails of side height of 110 mm.
Fastening of cables with clamp clip, type 2056.Magnetic shield insulation without cover 10 dB, with cover 15 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Tray wide span

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 14,6128 kg CO2e / 1 Meter

Colour zinc

Dimension 110 x 500

Dimension 110x500x6000

Dimension B 500 mm

Dimension L 6000 mm

Fastening of rung Fully riveted

Height 110 mm

Length 6000 mm

Maintain electrical functions no

Material Steel

Rail thickness 2 mm

Rung slot dimension 17,00

Rustproof steel, pickled no
Side perforation yes
Side rail version Profile (open)
Support spacing 3.0 m 2,9 kN/m
Support spacing 3.5 m 2,48 kN/m
Support spacing 4.0 m 2,1 kN/m
Support spacing 4.5 m 1,78 kN/m
Support spacing 5.0 m 1,5 kN/m
Support spacing 6.0 m 1 kN/m
Support spacing 7.0 m 0,7 kN/m
Surface Hot-dip galvanised
Usable cross-section 471 cm²
Usable cross-section 47100 mm²
Version of the rungs Profile perforated
Wide-span version yes
Width 500 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / WKLG 1150 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.