


**INDUSTRIAL COMPONENT DATA**

# WKLG 1630 FT 6227139 OBO BETTERMANN Wide clamping cable conductor perforated side rail, 160x300x6000, Hot-di..

Brand: OBO BETTERMANN | Manufacturer Part Number: WKLG 1630 FT



|                 |                                     |
|-----------------|-------------------------------------|
| Manufacturer    | OBO BETTERMANN                      |
| MPN / Reference | WKLG 1630 FT                        |
| Catalog number  | 6227139                             |
| Category        | Cable ladder/wide span cable ladder |
| Minimum order   | 6 m.                                |
| Document ID     | EO-1FFB25221E                       |
| Generated       | 2026-07-29                          |

## Product Overview

Wide clamping cable conductor perforated side rail, 160x300x6000, Hot-dip galvanised, DIN EN ISO 1461, Steel, St  
Wide span cable ladder WKLG 160 FT. Wide span cable ladder with perforated side rail of side height of 160 mm.  
Fastening of cables with clamp clip, type 2056.Magnetic shield insulation without cover 10 dB, with cover 15 dB.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Tray wide span**

## Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 17,4469 kg CO2e / 1 Meter

Colour zinc

Dimension 160 x 300

Dimension 160x300x6000

Dimension B 300 mm

Dimension L 6000 mm

Fastening of rung Fully riveted

Height 160 mm

Length 6000 mm

Maintain electrical functions no

Material Steel

Rail thickness 2 mm

Rung slot dimension 16,50

Rustproof steel, pickled no  
Side perforation yes  
Support spacing 3.0 m 2,9 kN/m  
Support spacing 3.5 m 2,59 kN/m  
Support spacing 4.0 m 2,3 kN/m  
Support spacing 4.5 m 2,04 kN/m  
Support spacing 5.0 m 1,8 kN/m  
Support spacing 6.0 m 1,4 kN/m  
Support spacing 7.0 m 1 kN/m  
Support spacing 8.0 m 0,7 kN/m  
Surface Hot-dip galvanised  
Usable cross-section 427 cm<sup>2</sup>  
Usable cross-section 42700 mm<sup>2</sup>  
Version of the rungs Profile unperforated  
Wide-span version yes  
Width 300 mm

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / WKLG 1630 FT with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.