

**INDUSTRIAL COMPONENT DATA**

# WKLG 1630 A4 6227172 OBO BETTERMANN Wide clamping cable conductor perforated side rail, 160x300x6000, Stainl..

Brand: OBO BETTERMANN | Manufacturer Part Number: WKLG 1630 A4



|                 |                                     |
|-----------------|-------------------------------------|
| Manufacturer    | OBO BETTERMANN                      |
| MPN / Reference | WKLG 1630 A4                        |
| Catalog number  | 6227172                             |
| Category        | Cable ladder/wide span cable ladder |
| Minimum order   | 6 m.                                |
| Document ID     | EO-4AE5425179                       |
| Generated       | 2026-08-01                          |

## Product Overview

Wide clamping cable conductor perforated side rail, 160x300x6000, Stainless steel, grade 316 Ti, VA, 1.4571  
WKLG 1630 A4 wide opening tray, perforated side part 160x300x6000 Stainless steel 1.4571, V4A, 1.4571, Polished, with post-treatment  
WKLG 160 A4 ladder tray with wide openings. Wide span ladder tray with perforated side flange height 110 mm. Fixing of cables and tubes with type 2056 clamp. Magnetic insulation without cap 10 dB, with cap 15 dB.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      OBO BETTERMANN &gt; KTS cable support systems - OBO BETTERMANN &gt; Tray wide span

## Additional Product Information

ETIM for 6227172 Cable tray, ladder and wire basket systems (EC000854)

Feature Name

Feature Value

Type of side joist (EF007666)

Channel (open)

Side perforation (EF001122)

Yes

Type of rung (EF001060)

Plain channel

Height (EF000040)

160 mm

Width (EF000008)

300 mm

Length (EF001438)

6000 mm

Useful cross section (EF005140)

42700 mm<sup>2</sup>

Suitable for circuit integrity (EF007806)

No

Vertical cable ladder (EF017249)

No

Material (EF002169)

Stainless steel

Material quality (EF001257)

Stainless steel 316 Ti (1.4571)

Surface protection (EF000139)

Untreated

Weight (EF000167)

7.67 kg/m

Safe working load according to IEC 61537 with support spacing 3.0 m (EF017267)

2900

Safe working load according to IEC 61537 with support spacing 4.0 m (EF017268)

2300

Safe working load according to IEC 61537 with support spacing 5.0 m (EF017269)

1800

Safe working load according to IEC 61537 with support spacing 6.0 m (EF017270)

1400

Safe working load according to IEC 61537 with support spacing 7.0 m (EF017271)

1000

Safe working load according to IEC 61537 with support spacing 8.0 m (EF017272)

700

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / WKLG 1630 A4 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.