

INDUSTRIAL COMPONENT DATA

WKLG 1630 A4 6227172 OBO BETTERMANN Wide clamping cable conductor perforated side rail, 160x300x6000, Stainl..

Brand: OBO BETTERMANN | Manufacturer Part Number: WKLG 1630 A4



Manufacturer	OBO BETTERMANN
MPN / Reference	WKLG 1630 A4
Catalog number	6227172
Category	Cable ladder/wide span cable ladder
Minimum order	6 m.
Document ID	EO-4AE5425179
Generated	2026-08-03

Product Overview

Wide clamping cable conductor perforated side rail, 160x300x6000, Stainless steel, grade 316 Ti, VA, 1.4571
WKLG 1630 A4 wide opening tray, perforated side part 160x300x6000 Stainless steel 1.4571, V4A, 1.4571, Polished, with post-treatment
WKLG 160 A4 ladder tray with wide openings. Wide span ladder tray with perforated side flange height 110 mm. Fixing of cables and tubes with type 2056 clamp. Magnetic insulation without cap 10 dB, with cap 15 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Tray wide span

Additional Product Information

ETIM for 6227172 Cable tray, ladder and wire basket systems (EC000854)

Feature Name

Feature Value

Type of side joist (EF007666)

Channel (open)

Side perforation (EF001122)

Yes

Type of rung (EF001060)

Plain channel

Height (EF000040)

160 mm

Width (EF000008)
300 mm
Length (EF001438)
6000 mm
Useful cross section (EF005140)
42700 mm²
Suitable for circuit integrity (EF007806)
No
Vertical cable ladder (EF017249)
No
Material (EF002169)
Stainless steel
Material quality (EF001257)
Stainless steel 316 Ti (1.4571)
Surface protection (EF000139)
Untreated
Weight (EF000167)
7.67 kg/m
Safe working load according to IEC 61537 with support spacing 3.0 m (EF017267)
2900
Safe working load according to IEC 61537 with support spacing 4.0 m (EF017268)
2300
Safe working load according to IEC 61537 with support spacing 5.0 m (EF017269)
1800
Safe working load according to IEC 61537 with support spacing 6.0 m (EF017270)
1400
Safe working load according to IEC 61537 with support spacing 7.0 m (EF017271)
1000
Safe working load according to IEC 61537 with support spacing 8.0 m (EF017272)
700

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / WKLG 1630 A4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.