

INDUSTRIAL COMPONENT DATA

WKLG 1650 A4 6227176 OBO BETTERMANN Wide clamping cable conductor perforated side rail, 160x500x6000, Stainl..

Brand: OBO BETTERMANN | Manufacturer Part Number: WKLG 1650 A4



Manufacturer	OBO BETTERMANN
MPN / Reference	WKLG 1650 A4
Catalog number	6227176
Category	Cable ladder/wide span cable ladder
Minimum order	6 m.
Document ID	EO-0D0753E5EA
Generated	2026-07-29

Product Overview

Wide clamping cable conductor perforated side rail, 160x500x6000, Stainless steel, grade 316 Ti, VA, 1.4571
WKLG 1650 A4 wide opening tray, perforated side part 160x500x6000 Stainless steel 1.4571, V4A, 1.4571, Polished, with subsequent treatment
WKLG 160 A4 ladder tray with wide openings. Wide span ladder tray with perforated side flange height 110 mm. Fixing of cables and tubes with type 2056 clamp. Magnetic insulation without cap 10 dB, with cap 15 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Tray wide span

Additional Product Information

ETIM for 6227176 Cable tray, ladder and wire basket systems (EC000854)

Feature Name

Feature Value

Type of side joist (EF007666)

Channel (open)

Side perforation (EF001122)

Yes

Type of rung (EF001060)

Plain channel

Height (EF000040)

160 mm

Width (EF000008)
500 mm

Length (EF001438)
6000 mm

Useful cross section (EF005140)
71700 mm²

Suitable for circuit integrity (EF007806)
No

Vertical cable ladder (EF017249)
No

Material (EF002169)
Stainless steel

Material quality (EF001257)
Stainless steel 316 Ti (1.4571)

Surface protection (EF000139)
Untreated

Weight (EF000167)
8.29 kg/m

Safe working load according to IEC 61537 with support spacing 3.0 m (EF017267)
3000

Safe working load according to IEC 61537 with support spacing 4.0 m (EF017268)
2500

Safe working load according to IEC 61537 with support spacing 5.0 m (EF017269)
2000

Safe working load according to IEC 61537 with support spacing 6.0 m (EF017270)
1600

Safe working load according to IEC 61537 with support spacing 7.0 m (EF017271)
1300

Safe working load according to IEC 61537 with support spacing 8.0 m (EF017272)
1000

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / WKLG 1650 A4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.