

INDUSTRIAL COMPONENT DATA

WKSG 120 A2 6098161 OBO BETTERMANN Wide clamping cable duct perforated, floor beaded, 110x200x6000, Stainles..

Brand: OBO BETTERMANN | Manufacturer Part Number: WKSG 120 A2



Manufacturer	OBO BETTERMANN
MPN / Reference	WKSG 120 A2
Catalog number	6098161
Category	Cable tray/wide span cable tray
Minimum order	6 m.
Document ID	EO-AE03483880
Generated	2026-08-03

Product Overview

Wide clamping cable duct perforated, floor beaded, 110x200x6000, Stainless steel, grade 304, VA, 1.4301

WKSG 120 A2 wide bay cable tray, perforated, corrugated floor 110x200x6000 Stainless steel 1.4301, A2, 1.4301, Polished, with subsequent treatment

WKSG 110 A2 wide-span cable tray. Cable tray system wide span, perforated, with 110 mm wing. Magnetic insulation without cover 20 dB, with cover 50 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Tray wide span

Additional Product Information

WKSG 110 = wide span cable tray system, perforated, with a side height of 110 mm

ETIM for 6098161 Cable tray, ladder and wire basket systems (EC000047)

Feature Name

Feature Value

Height (EF000040)

110 mm

Width (EF000008)

200 mm

Material thickness (EF000386)

2 mm

Length (EF001438)

6000 mm

Working length (EF006318)

6000 mm

Useful cross section (EF005140)

20200 mm²

Side perforation (EF001122)

Yes

Bottom perforation (EF004545)

Yes

Model (EF000010)

Coupler not included

Type of connector (EF000141)

Screwed

Suitable for circuit integrity (EF007806)

No

Material (EF002169)

Stainless steel

Material quality (EF001257)

Stainless steel 304

Surface protection (EF000139)

Untreated

Weight (EF000167)

7.14 kg/m

Possible support spacing (EF017261)

3 m

Safe working load according to IEC 61537 with support spacing 3.0 m (EF017267)

2500

Safe working load according to IEC 61537 with support spacing 4.0 m (EF017268)

1600

Safe working load according to IEC 61537 with support spacing 5.0 m (EF017269)

1100

Safe working load according to IEC 61537 with support spacing 6.0 m (EF017270)

750

Safe working load according to IEC 61537 with support spacing 7.0 m (EF017271)

450

Safe working load according to IEC 61537 with support spacing 8.0 m (EF017272)

200

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / WKSG 120 A2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.