


INDUSTRIAL COMPONENT DATA

WKSG 140 FS 6098119 OBO BETTERMANN Wide clamping cable duct perforated, floor beaded, 110x400x6000, Strip-ga..

Brand: OBO BETTERMANN | Manufacturer Part Number: WKSG 140 FS



Manufacturer	OBO BETTERMANN
MPN / Reference	WKSG 140 FS
Catalog number	6098119
Category	Cable tray/wide span cable tray
Minimum order	6 m.
Document ID	EO-D0ED4BB3BC
Generated	2026-08-01

Product Overview

Wide clamping cable duct perforated, floor beaded, 110x400x6000, Strip-galvanised, DIN EN 10147, Steel, St WKSG 140 FS wide opening cable tray, perforated, corrugated floor 110x400x6000 Steel, St, strip galvanized, DIN EN 10346

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Tray wide span**

Additional Product Information

WKSG 110 = wide span cable tray system, perforated, with a side height of 110 mm

ETIM for 6098119 Cable tray, ladder and wire basket systems (EC000047)

Feature Name

Feature Value

Height (EF000040)

110 mm

Width (EF000008)

400 mm

Material thickness (EF000386)

2 mm

Length (EF001438)

6000 mm

Working length (EF006318)

6000 mm
Useful cross section (EF005140)
40800 mm²
Side perforation (EF001122)
Yes
Bottom perforation (EF004545)
Yes
Model (EF000010)
Coupler not included
Type of connector (EF000141)
Screwed
Suitable for circuit integrity (EF007806)
No
Material (EF002169)
Steel
Surface protection (EF000139)
Pre-galvanised
Weight (EF000167)
9.22 kg/m
Possible support spacing (EF017261)
3 m
Safe working load according to IEC 61537 with support spacing 3.0 m (EF017267)
2900
Safe working load according to IEC 61537 with support spacing 4.0 m (EF017268)
2000
Safe working load according to IEC 61537 with support spacing 5.0 m (EF017269)
1500
Safe working load according to IEC 61537 with support spacing 6.0 m (EF017270)
1000
Safe working load according to IEC 61537 with support spacing 7.0 m (EF017271)
700
Safe working load according to IEC 61537 with support spacing 8.0 m (EF017272)
400

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / WKSG 140 FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.