

INDUSTRIAL COMPONENT DATA

WKSG 160 A2 6098177 OBO BETTERMANN Wide clamping cable duct perforated, floor beaded, 110x600x6000, Stainles..

Brand: OBO BETTERMANN | Manufacturer Part Number: WKSG 160 A2



Manufacturer	OBO BETTERMANN
MPN / Reference	WKSG 160 A2
Catalog number	6098177
Category	Cable tray/wide span cable tray
Minimum order	6 m.
Document ID	EO-88FB702FEC
Generated	2026-08-01

Product Overview

Wide clamping cable duct perforated, floor beaded, 110x600x6000, Stainless steel, grade 304, VA, 1.4301

WKSG 160 A2 wide opening cable tray, perforated, grooved floor 110x600x6000 Stainless steel 1.4301, A2, 1.4301, Polished, with subsequent treatment

Wide span cable tray WKSG 110 A2. Wide span cable tray system, perforated, with a side height of 110 mm.Magnetic shield insulation without cover 20 dB, with cover 50 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Tray wide span

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 58,4621 kg CO2e / 1 Meter

Colour stainless steel

Connector version Without connectors

Dimension 110 X 600

Dimension 110x600x6000

Dimension B 600 mm

Dimension L 6000 mm

Height 110 mm

Length 6000 mm

Magnetic shield insulation with cover 50 dB

Magnetic shield insulation without cover 20 dB

Maintain electrical functions no
Material Stainless steel 1.4301
Mounting perforation in base yes
Plate thickness 2 mm
Rustproof steel, pickled no
Side perforation yes
Support spacing 3.0 m 2,9 kN/m
Support spacing 3.5 m 2,43 kN/m
Support spacing 4.0 m 2 kN/m
Support spacing 4.5 m 1,72 kN/m
Support spacing 5.0 m 1,5 kN/m
Support spacing 6.0 m 1 kN/m
Support spacing 7.0 m 0,7 kN/m
Support spacing 8.0 m 0,4 kN/m
Surface Bright, treated
Type of connector, cable support system Screwed
Usable cross-section 61400 mm²
Usable cross-section 614 cm²
Usable length 6000 mm
Wide-span version yes
Width 600 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / WKSG 160 A2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.