

## INDUSTRIAL COMPONENT DATA

# WKSG 164 VA 4301 6098575 OBO BETTERMANN Wide clamping cable duct perforated, floor beaded, 160x400x6000, Sta..

Brand: OBO BETTERMANN | Manufacturer Part Number: WKSG 164 A2



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | OBO BETTERMANN                  |
| MPN / Reference | WKSG 164 A2                     |
| Catalog number  | 6098575                         |
| Category        | Cable tray/wide span cable tray |
| Minimum order   | 6 m.                            |
| Document ID     | EO-05B153844E                   |
| Generated       | 2026-08-03                      |

## Product Overview

Wide clamping cable duct perforated, floor beaded, 160x400x6000, Stainless steel, grade 304, VA, 1.4301  
Wide span cable tray WKSG 160 A2. Wide span cable tray system, perforated, with a side height of 160 mm. Magnetic shield insulation without cover 20 dB, with cover 50 dB.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                              |
|--------------|------------------------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Tray wide span |
|--------------|------------------------------------------------------------------------------|

## Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 54,5612 kg CO2e / 1 Meter

Colour stainless steel

Connector version Without connectors

Dimension 160 X 400

Dimension 160x400x6000

Dimension B 400 mm

Dimension L 6000 mm

Height 160 mm

Length 6000 mm

Magnetic shield insulation with cover 50 dB

Magnetic shield insulation without cover 20 dB

Maintain electrical functions no  
Material Stainless steel 1.4301  
Mounting perforation in base yes  
Plate thickness 2 mm  
Rustproof steel, pickled no  
Side perforation yes  
Support spacing 3.0 m 3 kN/m  
Support spacing 3.5 m 2,73 kN/m  
Support spacing 4.0 m 2,5 kN/m  
Support spacing 4.5 m 2,24 kN/m  
Support spacing 5.0 m 2 kN/m  
Support spacing 6.0 m 1,6 kN/m  
Support spacing 7.0 m 1,3 kN/m  
Support spacing 8.0 m 1 kN/m  
Surface Bright, treated  
Type of connector, cable support system Screwed  
Usable cross-section 608 cm<sup>2</sup>  
Usable cross-section 60800 mm<sup>2</sup>  
Usable length 6000 mm  
Wide-span version yes  
Width 400 mm

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / WKSG 164 A2 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.