

INDUSTRIAL COMPONENT DATA

LCIS 660 6 A2 6207260 OBO BETTERMANN TRAY LADDER TREAD PERFORATED, WELDED, LCIS 660 6 A2

Brand: OBO BETTERMANN | Manufacturer Part Number: LCIS 660 6 A2



Manufacturer	OBO BETTERMANN
MPN / Reference	LCIS 660 6 A2
Catalog number	6207260
Category	Cable ladder/wide span cable ladder
Minimum order	6 m.
Document ID	EO-D07E57C4DB
Generated	2026-08-04

Product Overview

TRAY LADDER TREAD PERFORATED, WELDED, LCIS 660 6 A2

Perforated step ladder tray, welded 60x600x6000, stainless steel 1.4301, A2, 1.4301

Cable ladder LCIS 60, 6 m C30 A2. Cable ladder with 60 mm side height with welded C30 profile rungs which are open in an upwards direction. Rolled side rail for reinforcement and as edge protection. Fastening to the bracket takes place using clamps, type LKS 40. The slot dimension of the frame is 16.5 mm and the appropriate clamp clip is type 2056. Magnetic shield insulation without cover 10 dB, with cover 15 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN
--------------	---

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 18,2782 kg CO2e / 1 Meter

Colour stainless steel

Dimension 60x600x6000

Dimension B 600 mm

Fastening of rung Welded

Height 60 mm

Length 6000 mm

Maintain electrical functions no

Material Stainless steel 1.4301

Rail thickness 1,5 mm

Rung distance 300 mm
Rung slot dimension 16,50
Rustproof steel, pickled yes
Side perforation yes
Side rail version Flat profile
Support spacing 1.5 m 3,3 kN/m
Support spacing 2.0 m 2 kN/m
Support spacing 2.5 m 1,3 kN/m
Support spacing 3.0 m 1 kN/m
Support spacing 3.5 m 0,78 kN/m
Support spacing 4.0 m 0,4 kN/m
Support spacing 4.5 m 0,3 kN/m
Support spacing 5.0 m 0,2 kN/m
Surface Bright, treated
Usable cross-section 24000 mm²
Usable cross-section 240 cm²
Version of the rungs Profile perforated
Wide-span version no
Width 600 mm
ETIM for 6207260 Cable tray, ladder and wire basket systems (EC000854)
Feature Name
Feature Value
Type of side joist (EF007666)
Flat profile
Side perforation (EF001122)
Yes
Type of rung (EF001060)
Slotted channel
Fixation rung (EF008307)
Welded
Height (EF000040)
60 mm
Width (EF000008)
600 mm
Length (EF001438)
6000 mm
Useful cross section (EF005140)
24000 mm²
Suitable for circuit integrity (EF007806)
No
Rung centre spacing (EF008185)
300 mm
Vertical cable ladder (EF017249)
No
Material (EF002169)
Stainless steel
Material quality (EF001257)

Stainless steel 304 (1.4301)

Surface protection (EF000139)

Untreated

Weight (EF000167)

3.54 kg/m

Possible support spacing (EF017261)

1.5 m

Safe working load ac...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / LCIS 660 6 A2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.