

INDUSTRIAL COMPONENT DATA

LK4 15015 6178001 OBO BETTERMANN Slotted cable trunking system , 15x15x2000, Stone grey, 7030, Polyvinylchlo..

Brand: OBO BETTERMANN | Manufacturer Part Number: LK4 15015



Manufacturer	OBO BETTERMANN
MPN / Reference	LK4 15015
Catalog number	6178001
Category	Slotted cable trunking system
Minimum order	72 m.
Document ID	EO-01208B1E35
Generated	2026-08-02

Product Overview

Slotted cable trunking system , 15x15x2000, Stone grey, 7030, Polyvinylchloride, PVC

LK4 15015 frame channel, 15x15x2000 Polyvinyl chloride, PVC,

Wiring trunking, type LK4 15015. Wiring duct, incl. cover and base perforation, for horizontal and vertical routing of electrical cables in the switchgear cabinet. Designed as a metric duct. The nominal dimension of the system size corresponds to the internal dimension of the duct. Retainers are broken out without tools. The flush-floor routing of cables is possible through predetermined break points. Tested to DIN EN 50085-2-3. Special lengths on request.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > LFS cable routing systems - OBO BETTERMANN > Channel box

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 0,2716 kg CO2e / 1 Meter

Colour Stone grey; RAL 7030

Creepage current-resistant yes

Dimension 15x15x2000

Fastening type Base perforation

Flexible no

Halogen-free no

Height 15 mm

Length 2000 mm
Material Polyvinylchloride
Permitted temperature range, max. 60 °C
Permitted temperature range, min. -5 °C
Self-extinguishing yes
Side wall version Profile (open)
Slot spacing 10 mm
Slot width 4 mm
Usable cross-section 1,9 cm²
Width 15 mm
With cover yes
ETIM for 6178001 Slotted cable trunking (EC000012)
Feature Name
Feature Value
Material (EF002169)
Polyvinyl chloride (PVC)
Height (EF000040)
15 mm
Width (EF000008)
15 mm
Length (EF001438)
2000 mm
Diameter (EF000551)
0 mm
Distance of slots (EF005246)
10 mm
Slit width (EF005247)
4 mm
Halogen free (EF000025)
No
Self-extinguishing (EF000681)
Yes
Flexible (EF000083)
No
Useful cross section (EF005140)
190 mm²
Type of fastening (EF002442)
Bottom perforation
With cover (EF007965)
Yes
Colour (EF000007)
Grey
RAL-number (EF000116)
7030

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / LK4 15015 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.