

INDUSTRIAL COMPONENT DATA

LK4 40060 6178014 OBO BETTERMANN Slotted cable trunking system , 40x60x2000, Stone grey, 7030, Polyvinylchlo..

Brand: OBO BETTERMANN | Manufacturer Part Number: LK4 40060



Manufacturer	OBO BETTERMANN
MPN / Reference	LK4 40060
Catalog number	6178014
Category	Slotted cable trunking system
Minimum order	24 m.
Document ID	EO-10A762BF6B
Generated	2026-08-02

Product Overview

Slotted cable trunking system , 40x60x2000, Stone grey, 7030, Polyvinylchloride, PVC
Wiring trunking, type LK4 40060. Wiring duct, incl. cover and base perforation, for horizontal and vertical routing of electrical cables in the switchgear cabinet. Designed as a metric duct. The nominal dimension of the system size corresponds to the internal dimension of the duct. Retainers are broken out without tools. The flush-floor routing of cables is possible through predetermined break points. Tested to DIN EN 50085-2-3. Special lengths on request.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > LFS cable routing systems - OBO BETTERMANN > Channel box
--------------	---

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 1,3577 kg CO2e / 1 Meter
Colour Stone grey; RAL 7030
Creepage current-resistant yes
Dimension 40x60x2000
Fastening type Base perforation
Flexible no
Halogen-free no
Height 40 mm
Length 2000 mm

Material Polyvinylchloride
Permitted temperature range, max. 60 °C
Permitted temperature range, min. -5 °C
Self-extinguishing yes
Side wall version Slotted
Slot spacing 10 mm
Slot width 4 mm
Usable cross-section 22,34 cm²
Width 60 mm
With cover yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / LK4 40060 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.