


INDUSTRIAL COMPONENT DATA

LK4 60120 6178039 OBO BETTERMANN Slotted cable trunking system , 60x120x2000, Stone grey, 7030, Polyvinylchl..

Brand: OBO BETTERMANN | Manufacturer Part Number: LK4 60120



Manufacturer	OBO BETTERMANN
MPN / Reference	LK4 60120
Catalog number	6178039
Category	Slotted cable trunking system
Minimum order	8 m.
Document ID	EO-C897D0119B
Generated	2026-08-02

Product Overview

Slotted cable trunking system , 60x120x2000, Stone grey, 7030, Polyvinylchloride, PVC

LK4 60120 frame channel, 60x120x2000 Polyvinyl chloride, PVC,

Wiring trunking, type LK4 60120. Wiring duct, incl. cover and base perforation, for horizontal and vertical routing of electrical cables in the switchgear cabinet. Designed as a metric duct. The nominal dimension of the system size corresponds to the internal dimension of the duct. Retainers are broken out without tools. The flush-floor routing of cables is possible through predetermined break points. Tested to DIN EN 50085-2-3. Special lengths on request.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > LFS cable routing systems - OBO BETTERMANN > Channel box

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 2,7547 kg CO2e / 1 Meter

Colour Stone grey; RAL 7030

Creepage current-resistant yes

Dimension 60x120x2000

Fastening type Base perforation

Flexible no

Halogen-free no

Height 60 mm

Length 2000 mm
Material Polyvinylchloride
Permitted temperature range, max. 60 °C
Permitted temperature range, min. -5 °C
Self-extinguishing yes
Side wall version Slotted
Slot spacing 10 mm
Slot width 4 mm
Usable cross-section 69,69 cm²
Width 120 mm
With cover yes
ETIM for 6178039 Slotted cable trunking (EC000012)
Feature Name
Feature Value
Material (EF002169)
Polyvinyl chloride (PVC)
Height (EF000040)
60 mm
Width (EF000008)
120 mm
Length (EF001438)
2000 mm
Diameter (EF000551)
0 mm
Distance of slots (EF005246)
10 mm
Slit width (EF005247)
4 mm
Type of side wall (EF000098)
Slotted
Halogen free (EF000025)
No
Self-extinguishing (EF000681)
Yes
Flexible (EF000083)
No
Useful cross section (EF005140)
6969 mm²
Type of fastening (EF002442)
Bottom perforation
With cover (EF007965)
Yes
Colour (EF000007)
Grey
RAL-number (EF000116)
7030

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / LK4 60120 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.