

## INDUSTRIAL COMPONENT DATA

# LK4 80040 6178052 OBO BETTERMANN Slotted cable trunking system , 80x40x2000, Stone grey, 7030, Polyvinylchlo..

Brand: OBO BETTERMANN | Manufacturer Part Number: LK4 80040



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | OBO BETTERMANN                |
| MPN / Reference | LK4 80040                     |
| Catalog number  | 6178052                       |
| Category        | Slotted cable trunking system |
| Minimum order   | 24 m.                         |
| Document ID     | EO-5BDFEA5B1D                 |
| Generated       | 2026-07-29                    |

## Product Overview

Slotted cable trunking system , 80x40x2000, Stone grey, 7030, Polyvinylchloride, PVC

Wiring trunking, type LK4 80040. Wiring duct, incl. cover and base perforation, for horizontal and vertical routing of electrical cables in the switchgear cabinet. Designed as a metric duct. The nominal dimension of the system size corresponds to the internal dimension of the duct. Retainers are broken out without tools. The flush-floor routing of cables is possible through predetermined break points. Tested to DIN EN 50085-2-3. Special lengths on request.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                           |
|--------------|---------------------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > LFS cable routing systems - OBO BETTERMANN > Channel box |
|--------------|---------------------------------------------------------------------------|

## Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 1,7177 kg CO2e / 1 Meter

Colour Stone grey; RAL 7030

Creepage current-resistant yes

Dimension 80x40x2000

Fastening type Base perforation

Flexible no

Halogen-free no

Height 80 mm

Length 2000 mm

Material Polyvinylchloride  
Permitted temperature range, max. 60 °C  
Permitted temperature range, min. -5 °C  
Self-extinguishing yes  
Side wall version Slotted  
Slot spacing 10 mm  
Slot width 4 mm  
Usable cross-section 30,54 cm<sup>2</sup>  
Width 40 mm  
With cover yes

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / LK4 80040 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.