

**INDUSTRIAL COMPONENT DATA**

# LK4 N 80100 6178233 OBO BETTERMANN Slotted cable trunking system , 80x100x2000, Stone grey, 7030, Polyvinylc..

Brand: OBO BETTERMANN | Manufacturer Part Number: LK4 N 80100



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | OBO BETTERMANN                |
| MPN / Reference | LK4 N 80100                   |
| Catalog number  | 6178233                       |
| Category        | Slotted cable trunking system |
| Minimum order   | 16 m.                         |
| Document ID     | EO-73D0D2E178                 |
| Generated       | 2026-08-02                    |

## Product Overview

Slotted cable trunking system , 80x100x2000, Stone grey, 7030, Polyvinylchloride, PVC  
Wiring trunking, type LK4 N 80100. Wiring duct, incl. cover and base perforation, for horizontal and vertical routing of electrical cables in the switchgear cabinet. Designed as a metric duct. The nominal dimension of the system size corresponds to the internal dimension of the duct. Retainers are broken out without tools. The flush-floor routing of cables is possible through predetermined break points. Tapering in the side slots prevents the cables from falling out. Tested to DIN EN 50085-2-3. Special lengths on request.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                           |
|--------------|---------------------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > LFS cable routing systems - OBO BETTERMANN > Channel box |
|--------------|---------------------------------------------------------------------------|

## Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 2,5881 kg CO2e / 1 Meter  
Colour Stone grey; RAL 7030  
Creepage current-resistant yes  
Dimension 80x100x2000  
Fastening type Base perforation  
Flexible no  
Halogen-free no  
Height 80 mm  
Length 2000 mm  
Material Polyvinylchloride

Permitted temperature range, max. 60 °C

Permitted temperature range, min. -5 °C

Self-extinguishing yes

Side wall version Slotted

Slot spacing 12,5 mm

Slot width 5 mm

Usable cross-section 78,03 cm<sup>2</sup>

Width 100 mm

With cover yes

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / LK4 N 80100 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.