


INDUSTRIAL COMPONENT DATA

LKV 75125 6178330 OBO BETTERMANN Slotted cable trunking system , 75x125x2000, Stone grey, 7030, Polyvinylchl..

Brand: OBO BETTERMANN | Manufacturer Part Number: LKV 75125



Manufacturer	OBO BETTERMANN
MPN / Reference	LKV 75125
Catalog number	6178330
Category	Slotted cable trunking system
Minimum order	8 m.
Document ID	EO-E294944972
Generated	2026-07-28

Product Overview

Slotted cable trunking system , 75x125x2000, Stone grey, 7030, Polyvinylchloride, PVC
Wiring trunking, type LKV 75125. Wiring duct according to DIN EN 50085-2-3, incl. cover and base perforation, for horizontal and vertical routing of electrical cables in the switchgear cabinet. Designed as a DIN duct. Retainers are broken out without tools. The flush-floor routing of cables is possible through predetermined break points. Tested to DIN EN 50085-2-3. Special lengths on request.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > LFS cable routing systems - OBO BETTERMANN > Channel box

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 2,8622 kg CO2e / 1 Meter
Colour Stone grey; RAL 7030
Dimension 75x125x2000
Fastening type Base perforation
Flexible no
Halogen-free no
Height 75 mm
Length 2000 mm
Material Polyvinylchloride

Permitted temperature range, max. 60 °C

Permitted temperature range, min. -5 °C

Self-extinguishing yes

Side wall version Slotted

Slot spacing 12,5 mm

Slot width 5 mm

Usable cross-section 83,57 cm²

Width 125 mm

With cover yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / LKV 75125 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.