

INDUSTRIAL COMPONENT DATA

ISST70140BEL 6290013 OBO BETTERMANN Service pole for lighting, 64x145x3000, Anodised, Aluminium, Alu

Brand: OBO BETTERMANN | Manufacturer Part Number: ISST70140BEL



Manufacturer	OBO BETTERMANN
MPN / Reference	ISST70140BEL
Catalog number	6290013
Category	Installation column
Minimum order	1 Pcs
Document ID	EO-C12ADE95E0
Generated	2026-07-29

Product Overview

Service pole for lighting, 64x145x3000, Anodised, Aluminium, Alu

Service pole, type ISST70140B. ISS twin aluminium service pole with a 76.5 mm system opening. Set consists of: 1 single-compartment pole with clamping fastening Total length: 3,315-3,480 mm 1 fastening option for lighting 1 ceiling fastening with clamping device 1 device installation profile Length: 1,000 mm 1 aluminium cover Length: 1,000 mm 1 ISSBP70140 floor plate The area for device installation is suitable to accept front-locking device installation sockets of the 71GD... series. The panel to fasten luminaires is attached at a height of 1,850 mm and its own height is 148 mm. It is possible to create various kinds of workplace or general room lighting using the standard wall brackets from lighting manufacturers. The following accessories can be used, depending on the mounting situation.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > LFS cable routing systems - OBO BETTERMANN > Columns
--------------	---

Additional Product Information

Adjustable yes
Cable entry Top/bottom
Ceiling mounting yes
Changes according to location no
CO2 Footprint (GWP) Cradle-to-Gate 100,7864 kg CO2e / 1 Piece
Colour aluminium
Continuous profile no
Cover width 76,5 mm

Dimension 3000x146x65
Fastening type Tension
Floor mounting yes
Halogen-free yes
Height 65 mm
Height compensation, max. 480 mm
Height compensation, min. 315 mm
Length 3000 mm
Material Aluminium
Number of compartments 1 St.
Number of usable covers 1
Pole height, max. 3480 mm
Pole height, min. 3315 mm
Pole shape Oval
Pre-wired no
Surface Anodised
Version for Single-sided
Width 146 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / ISST70140BEL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.