


INDUSTRIAL COMPONENT DATA

LG 112 VS6 A2 6216492 OBO BETTERMANN LG 112 VS6VA4301 LG 112 VS6VA4301

Brand: OBO BETTERMANN | Manufacturer Part Number: LG 112 VS6 A2



Manufacturer	OBO BETTERMANN
MPN / Reference	LG 112 VS6 A2
Catalog number	6216492
Category	Cable ladder/wide span cable ladder
Minimum order	6 m.
Document ID	EO-E9C433B4FB
Generated	2026-08-02

Product Overview

LG 112 VS6VA4301 LG 112 VS6VA4301

Perforated ladder tray, with step VS 110x200x6000, stainless steel 1.4301, A2, 1.4301

Cable ladder LG 110, 6 m VS A2. Cable ladder with perforated side rail of side height 110 mm with riveted C profile rungs, open in an upwards direction. Magnetic shield insulation without cover 10 dB, with cover 15 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 19,5008 kg CO2e / 1 Meter

Colour stainless steel

Dimension 110x200

Dimension 110x200x6000

Dimension B 200 mm

Fastening of rung Blind riveted

Height 110 mm

Length 6000 mm

Material Stainless steel 1.4301

Rail thickness 1,5 mm

Rung distance 300 mm

Rung slot dimension 17,00

Support spacing 2.0 m 3,1 kN/m
Support spacing 2.5 m 2 kN/m
Support spacing 3.0 m 1,3 kN/m
Support spacing 3.5 m 0,9 kN/m
Support spacing 4.0 m 0,6 kN/m
Support spacing 4.5 m 0,5 kN/m
Support spacing 5.0 m 0,45 kN/m
Support spacing 6.0 m 0,15 kN/m
Surface Bright, treated
Usable cross-section 188 cm²
Usable cross-section 18800 mm²
Wide-span version no
Width 200 mm
ETIM for 6216492 Cable tray, ladder and wire basket systems (EC000854)
Feature Name
Feature Value
Height (EF000040)
110 mm
Width (EF000008)
200 mm
Length (EF001438)
6000 mm
Useful cross section (EF005140)
18800 mm²
Rung centre spacing (EF008185)
300 mm
Vertical cable ladder (EF017249)
No
Material (EF002169)
Stainless steel
Material quality (EF001257)
Stainless steel 304 (1.4301)
Surface protection (EF000139)
Untreated
Weight (EF000167)
3.78 kg/m
Safe working load according to IEC 61537 with support spacing 2.0 m (EF017265)
3100
Safe working load according to IEC 61537 with support spacing 2.5 m (EF017266)
2000
Safe working load according to IEC 61537 with support spacing 3.0 m (EF017267)
1300
Safe working load according to IEC 61537 with support spacing 4.0 m (EF017268)
600
Safe working load according to IEC 61537 w...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / LG 112 VS6 A2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.