

INDUSTRIAL COMPONENT DATA

LG 620 VS 6 FS 6208627 OBO BETTERMANN TRAY LADDER LG 620 VS 6 FS

Brand: OBO BETTERMANN | Manufacturer Part Number: LG 620 VS 6 FS



Manufacturer	OBO BETTERMANN
MPN / Reference	LG 620 VS 6 FS
Catalog number	6208627
Category	Cable ladder/wide span cable ladder
Minimum order	6 m.
Document ID	EO-FC7F5F01A6
Generated	2026-08-04

Product Overview

TRAY LADDER LG 620 VS 6 FS

LG 620 VS 6 FS ladder tray, perforated, with step VS 60x200x6000 Steel, St, galvanized in band, DIN EN 10346

LG 620 VS 6 FS 6208627 Cable ladder LG 60, 3 m VS FS

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN
--------------	---

Additional Product Information

The cable ladder is shipped folded up.

Type LG 620 VS 6 FS

Width mm 200

Rail thickness mm 1,5

Pack. m 6

Weight kg/100 m 269,750

Item No. 6208627

ETIM for 6208627 Cable tray, ladder and wire basket systems (EC000854)

Feature Name

Feature Value

Type of side joist (EF007666)

Flat profile

Side perforation (EF001122)

Yes

Type of rung (EF001060)

Slotted channel

Fixation rung (EF008307)

Blind riveted

Height (EF000040)

60 mm

Width (EF000008)

200 mm

Length (EF001438)

6000 mm

Useful cross section (EF005140)

9800 mm²

Suitable for circuit integrity (EF007806)

Yes

Rung centre spacing (EF008185)

300 mm

Vertical cable ladder (EF017249)

Yes

Material (EF002169)

Steel

Surface protection (EF000139)

Pre-galvanised

Weight (EF000167)

2.67 kg/m

Possible support spacing (EF017261)

1.5 m

Safe working load according to IEC 61537 with support spacing 1.5 m (EF017264)

3100

Safe working load according to IEC 61537 with support spacing 2.0 m (EF017265)

2250

Safe working load according to IEC 61537 with support spacing 2.5 m (EF017266)

1500

Safe working load according to IEC 61537 with support spacing 3.0 m (EF017267)

1100

Safe working load according to IEC 61537 with support spacing 4.0 m (EF017268)

450

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / LG 620 VS 6 FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.