

INDUSTRIAL COMPONENT DATA

LG 650 VS 6 FT 6208659 OBO BETTERMANN TRAY LADDER LG 650 VS 6 FT

Brand: OBO BETTERMANN | Manufacturer Part Number: LG 650 VS 6 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	LG 650 VS 6 FT
Catalog number	6208659
Category	Cable ladder/wide span cable ladder
Minimum order	6 m.
Document ID	EO-2C61620685
Generated	2026-08-04

Product Overview

TRAY LADDER LG 650 VS 6 FT

Ladder tray, perforated, with step VS, 60x500x6000, hot-dip galvanized steel, DIN EN ISO 1461

Cable ladder LG 60, 6 m VS FT. Cable ladder with perforated side rail of side height 60 mm with riveted C profile frames, open in an upwards direction (VS version).Magnetic shield insulation without cover 10 dB, with cover 15 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN
--------------	---

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 7,8759 kg CO2e / 1 Meter

Colour zinc

Dimension 60x500x6000

Dimension 60x500x6000

Dimension B 500 mm

Fastening of rung Blind riveted

Height 60 mm

Length 6000 mm

Maintain electrical functions no

Material Steel

Rail thickness 1,5 mm

Rung distance 300 mm

Rung slot dimension 16,50
Rustproof steel, pickled no
Side perforation yes
Side rail version Flat profile
Support spacing 1.5 m 3,1 kN/m
Support spacing 2.0 m 2,25 kN/m
Support spacing 2.5 m 1,5 kN/m
Support spacing 3.0 m 1,1 kN/m
Support spacing 3.5 m 0,75 kN/m
Support spacing 4.0 m 0,45 kN/m
Support spacing 4.5 m 0,3 kN/m
Support spacing 5.0 m 0,15 kN/m
Surface Hot-dip galvanised
Usable cross-section 248 cm²
Usable cross-section 24800 mm²
Version of the rungs Profile perforated
Wide-span version no
Width 500 mm
ETIM for 6208659 Cable tray, ladder and wire basket systems (EC000854)
Feature Name
Feature Value
Type of side joist (EF007666)
Flat profile
Side perforation (EF001122)
Yes
Type of rung (EF001060)
Slotted channel
Fixation rung (EF008307)
Blind riveted
Height (EF000040)
60 mm
Width (EF000008)
500 mm
Length (EF001438)
6000 mm
Useful cross section (EF005140)
24800 mm²
Suitable for circuit integrity (EF007806)
No
Rung centre spacing (EF008185)
300 mm
Vertical cable ladder (EF017249)
Yes
Material (EF002169)
Steel
Surface protection (EF000139)
Hot dip galvanized

Weight (EF000167)

3.55 kg/m

Possible support spacing (EF017261)

1.5 m

Safe working load according to IEC 61537 with support spacing...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / LG 650 VS 6 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.