

INDUSTRIAL COMPONENT DATA

MKR 15 125 A2 6045836 OBO BETTERMANN BAND. CORD CONSTR. NAVAL , MKR 15 125VA4301

Brand: OBO BETTERMANN | Manufacturer Part Number: MKR 15 125 A2



Manufacturer	OBO BETTERMANN
MPN / Reference	MKR 15 125 A2
Catalog number	6045836
Category	Cable tray/wide span cable tray
Minimum order	2 m.
Document ID	EO-0A69B03206
Generated	2026-08-04

Product Overview

BAND. CORD CONSTR. NAVAL , MKR 15 125VA4301

Band. Constr. cable holder Naval MKR 15 125 A2, Thickness 1.25mm 15x125x2000 Stainless Steel 1.4301, A2, 1.4301, Polished, Post-Treated

Cable tray, marine standard A2. Cable tray for use in ship construction, produced according to the marine standard VG 88900-1.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN
--------------	---

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 10,5972 kg CO2e / 1 Meter

Colour stainless steel

Connector version Without connectors

Dimension 15 X 125

Dimension 15x125x2000

Dimension B 125 mm

Height 15 mm

Length 2000 mm

Load test type according to IEC 61537 Type II

Maintain electrical functions no

Material Stainless steel 1.4301

Mounting perforation in base yes
NATO hole pattern yes
Plate thickness 1,25 mm
Rustproof steel, pickled yes
Side perforation no
Support spacing 1.0 m 0,35 kN/m
Support spacing 1.5 m 0,15 kN/m
Surface Bright, treated
Type of connector, cable support system Screwed
Wide-span version no
Width 125 mm
With cover no
ETIM for 6045836 Cable tray, ladder and wire basket systems (EC000047)
Feature Name
Feature Value
Height (EF000040)
15 mm
Width (EF000008)
125 mm
Material thickness (EF000386)
1.25 mm
Length (EF001438)
2000 mm
With cover (EF007965)
No
Side perforation (EF001122)
No
Bottom perforation (EF004545)
Yes
NATO-mounting holes (EF006059)
Yes
Model (EF000010)
Coupler not included
Type of connector (EF000141)
Screwed
Suitable for circuit integrity (EF007806)
No
Material (EF002169)
Stainless steel
Material quality (EF001257)
Stainless steel 304
Surface protection (EF000139)
Untreated
Weight (EF000167)
1.13 kg/m
Load test type according to IEC 61537 (EF015362)
Type II

Safe working load according to IEC 61537 with support spacing 1.0 m (EF017263)

350

Safe working load according to IEC 61537 with support spacing 1.5 m (EF017264)

150

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / MKR 15 125 A2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.