

INDUSTRIAL COMPONENT DATA

MKR 15 200 FS 6046002 OBO BETTERMANN BAND. CORD CONSTR. NAVAL MKR 15 200 FS

Brand: OBO BETTERMANN | Manufacturer Part Number: MKR 15 200 FS



Manufacturer	OBO BETTERMANN
MPN / Reference	MKR 15 200 FS
Catalog number	6046002
Category	Cable tray/wide span cable tray
Minimum order	2 m.
Document ID	EO-66037466AE
Generated	2026-08-03

Product Overview

BAND. CORD CONSTR. NAVAL MKR 15 200 FS

Band. Constr. cable holder Naval MKR 15 200 FS, Thickness 1.00mm 15x200x2000 Steel, St, galvanized in strip, DIN EN 10346

Cable tray, marine standard FS. Cable tray for use in ship construction, produced according to the marine standard VG 88900-1.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN
--------------	---

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 3,9754 kg CO2e / 1 Meter

Colour zinc

Connector version Without connectors

Dimension 15 x 200

Dimension 15x200x2000

Dimension B 200 mm

Height 15 mm

Length 2000 mm

Load test type according to IEC 61537 Type II

Maintain electrical functions no

Material Steel

Mounting perforation in base yes
NATO hole pattern yes
Plate thickness 1 mm
Rustproof steel, pickled no
Side perforation no
Support spacing 1.0 m 0,35 kN/m
Support spacing 1.0 m 1,1 kN/m
Support spacing 1.5 m 0,1 kN/m
Surface Strip galvanized
Type of connector, cable support system Screwed
Wide-span version no
Width 200 mm
With cover no
ETIM for 6046002 Cable tray, ladder and wire basket systems (EC000047)
Feature Name
Feature Value
Height (EF000040)
15 mm
Width (EF000008)
200 mm
Material thickness (EF000386)
1 mm
Length (EF001438)
2000 mm
With cover (EF007965)
No
Side perforation (EF001122)
No
Bottom perforation (EF004545)
Yes
NATO-mounting holes (EF006059)
Yes
Model (EF000010)
Coupler not included
Type of connector (EF000141)
Screwed
Suitable for circuit integrity (EF007806)
No
Material (EF002169)
Steel
Surface protection (EF000139)
Pre-galvanised
Weight (EF000167)
1.3 kg/m
Load test type according to IEC 61537 (EF015362)
Type II
Safe working load according to IEC 61537 with support spacing 1.0 m (EF017263)

350

Safe working load according to IEC 61537 with support spacing 1.5 m (EF017264)

100

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / MKR 15 200 FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.