

INDUSTRIAL COMPONENT DATA

MKS 315 FS 6053572 OBO BETTERMANN CABLE TRAY MKS MKS 315 FS

Brand: OBO BETTERMANN | Manufacturer Part Number: MKS 315 FS



Manufacturer	OBO BETTERMANN
MPN / Reference	MKS 315 FS
Catalog number	6053572
Category	Cable tray/wide span cable tray
Minimum order	3 m.
Document ID	EO-71FA35B4B7
Generated	2026-08-01

Product Overview

CABLE TRAY MKS MKS 315 FS

MKS MKS 315 FS cable tray, perforated 35x150x3000 Steel, St, galvanized in band, DIN EN 10346

MKS 315 FS 6053572 Cable tray MKS 35 FS

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN

Additional Product Information

FS version includes RV 35 straight connector set.

Type MKS 315 FS

Width mm 150

Plate thickness mm 1

Pack. m 3

Weight kg/100 m 177,067

Item No. 6053572

ETIM for 6053572 Cable tray, ladder and wire basket systems (EC000047)

Feature Name

Feature Value

Height (EF000040)

35 mm

Width (EF000008)

150 mm

Material thickness (EF000386)

1 mm

Length (EF001438)

3000 mm

Useful cross section (EF005140)

5050 mm²

With cover (EF007965)

No

Side perforation (EF001122)

Yes

Bottom perforation (EF004545)

Yes

NATO-mounting holes (EF006059)

No

Model (EF000010)

Coupler included

Type of connector (EF000141)

Screwed

Suitable for circuit integrity (EF007806)

No

Material (EF002169)

Steel

Surface protection (EF000139)

Pre-galvanised

Weight (EF000167)

1.77 kg/m

Load test type according to IEC 61537 (EF015362)

Type II

Possible support spacing (EF017261)

1 m

Safe working load according to IEC 61537 with support spacing 1.0 m (EF017263)

1200

Safe working load according to IEC 61537 with support spacing 1.5 m (EF017264)

750

Safe working load according to IEC 61537 with support spacing 2.0 m (EF017265)

550

Safe working load according to IEC 61537 with support spacing 2.5 m (EF017266)

300

Safe working load according to IEC 61537 with support spacing 3.0 m (EF017267)

200

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / MKS 315 FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.