

INDUSTRIAL COMPONENT DATA

MKS 615 FT 6055559 OBO BETTERMANN CABLE TRAY MKS MKS 615 FT

Brand: OBO BETTERMANN | Manufacturer Part Number: MKS 615 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	MKS 615 FT
Catalog number	6055559
Category	Cable tray/wide span cable tray
Minimum order	3 m.
Document ID	EO-3637F81A56
Generated	2026-07-29

Product Overview

CABLE TRAY MKS MKS 615 FT

MKS cable tray, perforated, 60x150x3000, hot dip galvanized steel, DIN EN ISO 1461

Cable tray MKS 60 FT. MKS 60 = Medium-duty cable tray system with a side height of 60 mm.Magnetic shield insulation without cover 20 dB, with cover 50 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN
--------------	---

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 5,3645 kg CO2e / 1 Meter

Colour zinc

Connector version Without connectors

Dimension 60x150x3000

Dimension 60 x 150

Dimension B 150 mm

Dimension W 150 mm

Height 2 in

Height 60 mm

Length 10 ft

Length 3000 mm

Load test type according to IEC 61537 Type II

Maintain electrical functions no
Material Steel
Mounting perforation in base yes
NATO hole pattern no
Plate thickness 0,04 in
Plate thickness 1 mm
Rustproof steel, pickled no
Side perforation yes
Support spacing 1.5 m 1,5 kN/m
Support spacing 1.75 m 1,25 kN/m
Support spacing 2.0 m 1 kN/m
Support spacing 2.5 m 0,5 kN/m
Surface Hot-dip galvanised
Type of connector, cable support system Screwed
Usable cross-section 8800 mm²
Usable cross-section 88 cm²
Wide-span version no
Width 150 mm
Width 6 in
With cover no
ETIM for 6055559 Cable tray, ladder and wire basket systems (EC000047)
Feature Name
Feature Value
Height (EF000040)
60 mm
Width (EF000008)
150 mm
Material thickness (EF000386)
1 mm
Length (EF001438)
3000 mm
Useful cross section (EF005140)
8800 mm²
With cover (EF007965)
No
Side perforation (EF001122)
Yes
Bottom perforation (EF004545)
Yes
NATO-mounting holes (EF006059)
No
Model (EF000010)
Coupler not included
Type of connector (EF000141)
Screwed
Suitable for circuit integrity (EF007806)
No

Material (EF002169)

Steel

Surface protection (EF000139)

Hot dip galvanized

Weight (EF000167)

2.26 kg/m

Load test type according to IEC 61537 (EF015362)

Type II

Possible support spacing (EF017261)

1.5 m

Safe....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / MKS 615 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.