

INDUSTRIAL COMPONENT DATA

MKS 630 FS 6055303 OBO BETTERMANN CABLE TRAY MKS MKS 630 FS

Brand: OBO BETTERMANN | Manufacturer Part Number: MKS 630 FS



Manufacturer	OBO BETTERMANN
MPN / Reference	MKS 630 FS
Catalog number	6055303
Category	Cable tray/wide span cable tray
Minimum order	3 m.
Document ID	EO-E47F958E65
Generated	2026-08-01

Product Overview

CABLE TRAY MKS MKS 630 FS

Mks cable tray, perforated, with joint set, 60x300x3000, galvanized steel in band, DIN EN 10346

Cable tray MKS 60 FS. MKS 60 = medium-duty cable tray system with a side height of 60 mm. Magnetic shield insulation without cover 20 dB, with cover 50 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 8,0321 kg CO2e / 1 Meter

Colour zinc

Connector version Without connectors

Dimension 60 x 300

Dimension 60x300x3000

Dimension B 300 mm

Dimension W 300 mm

Height 2 in

Height 60 mm

Length 3000 mm

Length 10 ft

Load test type according to IEC 61537 Type II

Maintain electrical functions no
Material Steel
Mounting perforation in base yes
NATO hole pattern no
Plate thickness 0,04 in
Plate thickness 1 mm
Rustproof steel, pickled no
Side perforation yes
Support spacing 1.5 m 1,5 kN/m
Support spacing 1.75 m 1,25 kN/m
Support spacing 2.0 m 1 kN/m
Support spacing 2.5 m 0,5 kN/m
Surface Strip galvanized
Type of connector, cable support system Screwed
Usable cross-section 178 cm²
Usable cross-section 17800 mm²
Wide-span version no
Width 12 in
Width 300 mm
With cover no
ETIM for 6055303 Cable tray, ladder and wire basket systems (EC000047)
Feature Name
Feature Value
Height (EF000040)
60 mm
Width (EF000008)
300 mm
Material thickness (EF000386)
1 mm
Length (EF001438)
3000 mm
Useful cross section (EF005140)
17800 mm²
With cover (EF007965)
No
Side perforation (EF001122)
Yes
Bottom perforation (EF004545)
Yes
NATO-mounting holes (EF006059)
No
Model (EF000010)
Coupler included
Type of connector (EF000141)
Screwed
Suitable for circuit integrity (EF007806)
No

Material (EF002169)

Steel

Surface protection (EF000139)

Pre-galvanised

Weight (EF000167)

3.13 kg/m

Load test type according to IEC 61537 (EF015362)

Type II

Possible support spacing (EF017261)

1.5 m

Safe workin...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / MKS 630 FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.