

INDUSTRIAL COMPONENT DATA

MKSU 615 FS 6063179 OBO BETTERMANN CABLE TRAY

MKSU MKSU 615 FS

Brand: OBO BETTERMANN | Manufacturer Part Number: MKSU 615 FS



Manufacturer	OBO BETTERMANN
MPN / Reference	MKSU 615 FS
Catalog number	6063179
Category	Cable tray/wide span cable tray
Minimum order	3 m.
Document ID	EO-BE53FB4BA4
Generated	2026-08-04

Product Overview

CABLE TRAY MKSU MKSU 615 FS

Mksu tray, without perfora.,with aguj. bonding, 60x150x3000, galvanized steel in band, DIN EN 10346

Cable tray MKSU 60 FS. MKSU 60 = medium-duty cable tray system, unperforated, with a side height of 60 mm. Straight connectors should be ordered in the appropriate quantity. Magnetic shield insulation without cover 20 dB, with cover 50 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN
--------------	---

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 5,2008 kg CO2e / 1 Meter

Colour zinc

Connector version Without connectors

Dimension 60 x 150

Dimension 60x150x3000

Dimension B 150 mm

Height 2 in

Height 60 mm

Length 10 ft

Length 3000 mm

Load test type according to IEC 61537 Type II

Maintain electrical functions no

Material Steel
Mounting perforation in base no
NATO hole pattern no
Plate thickness 0,04 in
Plate thickness 1 mm
Rustproof steel, pickled no
Side perforation no
Support spacing 1.5 m 1,5 kN/m
Support spacing 1.75 m 1,25 kN/m
Support spacing 2.0 m 1 kN/m
Support spacing 2.5 m 0,5 kN/m
Surface Strip galvanized
Type of connector, cable support system Screwed
Usable cross-section 8800 mm²
Usable cross-section 88 cm²
Wide-span version no
Width 6 in
Width 150 mm
With cover no
ETIM for 6063179 Cable tray, ladder and wire basket systems (EC000047)
Feature Name
Feature Value
Height (EF000040)
60 mm
Width (EF000008)
150 mm
Material thickness (EF000386)
1 mm
Length (EF001438)
3000 mm
Useful cross section (EF005140)
8800 mm²
With cover (EF007965)
No
Side perforation (EF001122)
No
Bottom perforation (EF004545)
No
NATO-mounting holes (EF006059)
No
Model (EF000010)
Coupler not included
Type of connector (EF000141)
Screwed
Suitable for circuit integrity (EF007806)
No
Material (EF002169)

Steel
Surface protection (EF000139)
Pre-galvanised
Weight (EF000167)
2.29 kg/m
Load test type according to IEC 61537 (EF015362)
Type II
Possible support spacing (EF017261)
1.5 m
Safe working load according to IEC...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / MKSU 615 FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.