

INDUSTRIAL COMPONENT DATA

MKSU 630 FT 6064396 OBO BETTERMANN CABLE TRAY

MKSU MKSU 630 FT

Brand: OBO BETTERMANN | Manufacturer Part Number: MKSU 630 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	MKSU 630 FT
Catalog number	6064396
Category	Cable tray/wide span cable tray
Minimum order	3 m.
Document ID	EO-A01CD7964D
Generated	2026-08-01

Product Overview

CABLE TRAY MKSU MKSU 630 FT

MKSU MKSU 630 FT cable tray, blind 60x300x3000 Steel, St, Hot dip galvanized, DIN EN ISO 1461

Cable tray MKSU 60 FT. MKSU 60 = Medium duty cable tray system, unperforated, with a side height of 60 mm.Magnetic shield insulation without cover 20 dB, with cover 50 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN
--------------	---

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 8,2532 kg CO2e / 1 Meter

Colour zinc

Connector version Without connectors

Dimension 60x300x3000

Height 60 mm

Height 2 in

Length 3000 mm

Length 10 ft

Load test type according to IEC 61537 Type II

Maintain electrical functions no

Material Steel

Mounting perforation in base no

NATO hole pattern no
Plate thickness 1 mm
Plate thickness 0,04 in
Rustproof steel, pickled no
Side perforation no
Support spacing 1.5 m 1,5 kN/m
Support spacing 1.75 m 1,25 kN/m
Support spacing 2.0 m 1 kN/m
Support spacing 2.5 m 0,5 kN/m
Surface Hot-dip galvanised
Type of connector, cable support system Screwed
Usable cross-section 17800 mm²
Usable cross-section 178 cm²
Wide-span version no
Width 300 mm
Width 12 in
With cover no
ETIM for 6064396 Cable tray, ladder and wire basket systems (EC000047)
Feature Name
Feature Value
Height (EF000040)
60 mm
Width (EF000008)
300 mm
Material thickness (EF000386)
1 mm
Length (EF001438)
3000 mm
Useful cross section (EF005140)
17800 mm²
With cover (EF007965)
No
Side perforation (EF001122)
No
Bottom perforation (EF004545)
No
NATO-mounting holes (EF006059)
No
Model (EF000010)
Coupler not included
Type of connector (EF000141)
Screwed
Suitable for circuit integrity (EF007806)
No
Material (EF002169)
Steel
Surface protection (EF000139)

Hot dip galvanized
Weight (EF000167)
3.78 kg/m
Load test type according to IEC 61537 (EF015362)
Type II
Possible support spacing (EF017261)
1.5 m
Safe working load according to IEC 61537 with support spacing....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / MKSU 630 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.