

## INDUSTRIAL COMPONENT DATA

# MSL4141PP3000FT 1123003 OBO BETTERMANN PROFILE MS 41 LS 3M 2 FT

Brand: OBO BETTERMANN | Manufacturer Part Number: MSL4141PP3000FT



|                 |                        |
|-----------------|------------------------|
| Manufacturer    | OBO BETTERMANN         |
| MPN / Reference | MSL4141PP3000FT        |
| Catalog number  | 1123003                |
| Category        | Mounting rail/-profile |
| Minimum order   | 3 m.                   |
| Document ID     | EO-AC5017D36D          |
| Generated       | 2026-08-01             |

## Product Overview

PROFILE MS 41 LS 3M 2 FT

Profile MSL4141PP3000FT, perfor., groove width 22mm 3000x41x41 Steel, St, Hot dip galvanized, DIN EN ISO 1461  
MS 41 LS 3M 2 FT 1123003 MS4141 mounting rail, slot width 22 mm, FS, side-perforated

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                        |
|--------------|------------------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN |
|--------------|------------------------------------------------------------------------|

## Additional Product Information

Heavy-duty C profile rail for individual installation of support constructions, e.g. for cable trays or as a panel for switchgear cabinets. Can also be used for cable routing, in conjunction with clamp clips with a U foot.

Type MSL4141PP3000FT

Length mm 3000

Dimension W x H mm 41x41

Material thickness mm 2

Dimension L mm 3000

Pack. m 3

Weight kg/100 m 191,500

ETIM for 1123003 Fixings and fasteners (EC000386)

Feature Name

Feature Value

Length (EF001438)

3000 mm  
Width (EF000008)  
41 mm  
Height (EF000040)  
41 mm  
Material thickness (EF000386)  
2 mm  
Profile shape (EF005179)  
C-profile  
Type of perforation (EF004147)  
3 sides perforated  
With toothing (EF000571)  
Yes  
Area moment of inertia  $I_y$  (EF012513)  
5.13 cm<sup>4</sup>  
Area of inertia  $I_z$  (EF012514)  
5.88 cm<sup>4</sup>  
Moment of resistance  $W_y$  (EF012503)  
2.49 cm<sup>3</sup>  
Moment of resistance  $W_z$  (EF012504)  
2.88 cm<sup>3</sup>  
Suitable for circuit integrity (EF007806)  
No  
Material (EF002169)  
Steel  
Surface protection (EF000139)  
Hot dip galvanized  
Weight (EF000167)  
1.92 kg

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / MSL4141PP3000FT with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.