

INDUSTRIAL COMPONENT DATA

2064 GTPL 2M 1115065 OBO BETTERMANN Carrier rail perforated, 2000x32x15, Electrogalvanised, transparently pa..

Brand: OBO BETTERMANN | Manufacturer Part Number: 2064 GTPL 2M



Manufacturer	OBO BETTERMANN
MPN / Reference	2064 GTPL 2M
Catalog number	1115065
Category	Mounting rail
Minimum order	2 m.
Document ID	EO-70CB2B742B
Generated	2026-08-02

Product Overview

Carrier rail perforated, 2000x32x15, Electrogalvanised, transparently passivated, Steel, St
Support rail, perforated GTP. G rail G32 to DIN EN 50035 (previously DIN 46277 Part 1)Support rail width 32 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > Profile picture

Additional Product Information

Bundle 20 m
CO2 Footprint (GWP) Cradle-to-Gate 1,3353 kg CO2e / 1 Meter
Dimension 2000x32x15
Drill hole spacing, centre 25 mm
Height 15 mm
Hole shape (ETIM) Long slot
Length 2000 mm
Material Steel
Material thickness 1,5 mm
Surface Electrogalvanized, transparently passivated
Version for Perforated
Version, rails G rail
Width 32 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 2064 GTPL 2M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.