

INDUSTRIAL COMPONENT DATA

2069 15 1.5 GTP 1115421 OBO BETTERMANN Top hat rail unperforated, 1.5 mm thick, 2000x35x15, Electrogalvanise..

Brand: OBO BETTERMANN | Manufacturer Part Number: 2069 15 1.5 GTP



Manufacturer	OBO BETTERMANN
MPN / Reference	2069 15 1.5 GTP
Catalog number	1115421
Category	Mounting rail
Minimum order	20 m.
Document ID	EO-CAC224913F
Generated	2026-08-01

Product Overview

Top hat rail unperforated, 1.5 mm thick, 2000x35x15, Electrogalvanised, transparently passivated, Steel, St
 Hat profile rail, unperforated GTP. Hat profile rail 35 x 15 mm similar to DIN EN 60715 (formerly DIN EN 50022), but with material thickness 1.5 mm.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > Profile picture

Additional Product Information

Bundle 20 m
 CO2 Footprint (GWP) Cradle-to-Gate 1,1921 kg CO2e / 1 Meter
 Dimension 2000x35x15
 Height 15 mm
 Hole shape (ETIM) Without
 Length 2000 mm
 Material Steel
 Material thickness 1,5 mm
 Surface Electrogalvanized, transparently passivated
 Version for Unperforated
 Version, rails Support rail DIN EN 60715
 Width 35 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 2069 15 1.5 GTP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.