

INDUSTRIAL COMPONENT DATA

2069 2M GTP 1115650 OBO BETTERMANN Top hat rail unperforated, 2000x35x7,5, Electrogalvanised, transparently ..

Brand: OBO BETTERMANN | Manufacturer Part Number: 2069 2M GTP



Manufacturer	OBO BETTERMANN
MPN / Reference	2069 2M GTP
Catalog number	1115650
Category	Mounting rail
Minimum order	50 m.
Document ID	EO-D34FDF0B35
Generated	2026-08-01

Product Overview

Top hat rail unperforated, 2000x35x7,5, Electrogalvanised, transparently passivated, Steel, St
 Hat profile rail, unperforated GTP. Hat profile rail 35 x 7.5 mm to DIN EN 60715 (formerly DIN EN 50022).

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > Profile picture

Additional Product Information

Bundle 50 m
 CO2 Footprint (GWP) Cradle-to-Gate 0,626 kg CO2e / 1 Meter
 Dimension 2000x35x7,5
 Height 7,5 mm
 Hole shape (ETIM) Without
 Length 2000 mm
 Material Steel
 Material thickness 1 mm
 Surface Electrogalvanized, transparently passivated
 Version for Unperforated
 Version, rails Support rail DIN EN 60715
 Width 35 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 2069 2M GTP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.