

INDUSTRIAL COMPONENT DATA

2069 2M GTPL 1115669 OBO BETTERMANN Top hat rail perforated, 2000x35x7,5, Electrogalvanised, transparently p..

Brand: OBO BETTERMANN | Manufacturer Part Number: 2069 2M GTPL



Manufacturer	OBO BETTERMANN
MPN / Reference	2069 2M GTPL
Catalog number	1115669
Category	Mounting rail
Minimum order	50 m.
Document ID	EO-E46EF3FA55
Generated	2026-08-03

Product Overview

Top hat rail perforated, 2000x35x7,5, Electrogalvanised, transparently passivated, Steel, St
Profile 2069 2M GTPL, perforated 2000x35x7.5 Steel, St, Galvanized, transparent passivated
DIN rail, GTPL perforated. DIN rail 35 x 7.5 mm according to DIN EN 60715 (formerly DIN EN 50022).

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > Profile picture**

Additional Product Information

Hat profile rail 35 x 7.5 mm to DIN en 60715 (formerly DIN en 50022).

ETIM for 1115669 Power distribution systems (EC001285)

Feature Name

Feature Value

Material (EF002169)

Steel

Surface protection (EF000139)

Galvanic/electrolytic zinc plated

Punch shape (EF001457)

Long-slot

Drill hole distance centrally (EF002677)

25 mm

Material thickness (EF000386)

1 mm

Length (EF001438)

2000 mm

Height (EF000040)

7.5 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 2069 2M GTPL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.