

**INDUSTRIAL COMPONENT DATA**

# EKS 620 FS 6056229 OBO BETTERMANN Cable tray EKS perforated, 60x200x3000, Strip-galvanised, DIN EN 10147, St..

Brand: OBO BETTERMANN | Manufacturer Part Number: EKS 620 FS



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | OBO BETTERMANN                  |
| MPN / Reference | EKS 620 FS                      |
| Catalog number  | 6056229                         |
| Category        | Cable tray/wide span cable tray |
| Minimum order   | 3 m.                            |
| Document ID     | EO-C13FBD1A10                   |
| Generated       | 2026-08-01                      |

## Product Overview

Cable tray EKS perforated, 60x200x3000, Strip-galvanised, DIN EN 10147, Steel, St  
EKS EKS 620 FS sheet metal tray, perforated 60x200x3000 Steel, St, strip galvanized, DIN EN 10346  
Cable tray EKS 60 FS. EKS 60 = extra-heavy cable tray system with 60 mm side height.Magnetic shield insulation without cover 20 dB, with cover 50 dB.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path OBO BETTERMANN &gt; KTS cable support systems - OBO BETTERMANN &gt; Rest sheet tray

## Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 13,249 kg CO2e / 1 Meter  
Colour zinc  
Connector version Without connectors  
Dimension 60 x 200  
Dimension 60x200x3000  
Dimension B 200 mm  
Height 60 mm  
Height 2 in  
Length 3000 mm  
Length 118 ft  
Load test type according to IEC 61537 Type II  
Maintain electrical functions no

Material Steel  
Mounting perforation in base yes  
NATO hole pattern no  
Plate thickness 2 mm  
Plate thickness 0,1 in  
Rustproof steel, pickled no  
Side perforation yes  
Support spacing 1.5 m 3,3 kN/m  
Support spacing 2.0 m 2,2 kN/m  
Support spacing 2.5 m 1,6 kN/m  
Support spacing 3.0 m 0,95 kN/m  
Surface Strip galvanized  
Type of connector, cable support system Screwed  
Usable cross-section 11800 mm<sup>2</sup>  
Usable cross-section 118 cm<sup>2</sup>  
Wide-span version no  
Width 200 mm  
Width 8 in  
With cover no

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / EKS 620 FS with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.