

## INDUSTRIAL COMPONENT DATA

# MKSM 115 FT 6059175 OBO BETTERMANN Cable tray MKSM perforated with quick connector, 110x150x3050, Hot-dip ga..

Brand: OBO BETTERMANN | Manufacturer Part Number: MKSM 115 FT



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | OBO BETTERMANN                  |
| MPN / Reference | MKSM 115 FT                     |
| Catalog number  | 6059175                         |
| Category        | Cable tray/wide span cable tray |
| Minimum order   | 3 m.                            |
| Document ID     | EO-752E0EDD39                   |
| Generated       | 2026-07-29                      |

## Product Overview

Cable tray MKSM perforated with quick connector, 110x150x3050, Hot-dip galvanised, DIN EN ISO 1461, Steel, St MKSM MKSM 115 FT cable tray, perforated, with needle. 110x150x3050 Steel, St, Hot-dip galvanized, DIN EN ISO 1461 Cable tray MKS-Magic® 110 FT. Cable tray with integrated quick fastening system. The usable length of the cable tray is 3,000 mm. The cable tray has continuous side perforations of 7 x 20 mm for the installation of additional connection and mounting components. From a cable tray width of 200 mm with 30% hole surface, suitable for use under sprinkler systems according to VdS guideline 2092.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                               |
|--------------|-------------------------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Rest sheet tray |
|--------------|-------------------------------------------------------------------------------|

## Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 7,2262 kg CO2e / 1 Meter

Colour zinc

Connector version Integrated connector

Dimension 110x150x3050

Dimension B 150 mm

Dimension L 30 mm

Dimension x 46 mm

Dimension y 112 mm

Height 110 mm

Length 3050 mm

Load test type according to IEC 61537 Type II  
Magnetic shield insulation with cover 50 dB  
Magnetic shield insulation without cover 20 dB  
Maintain electrical functions no  
Material Steel  
Mounting perforation in base yes  
NATO hole pattern no  
Plate thickness 1 mm  
Rustproof steel, pickled no  
Side perforation yes  
Support spacing 1.5 m 2 kN/m  
Support spacing 2.0 m 1,5 kN/m  
Support spacing 3.0 m 0,7 kN/m  
Surface Hot-dip galvanised  
Type of connector, cable support system Click fastening  
Usable cross-section 161 cm<sup>2</sup>  
Usable cross-section 16100 mm<sup>2</sup>  
Usable length 3000 mm  
Wide-span version no  
Width 150 mm  
With cover no  
ETIM for 6059175 Cable tray, ladder and wire basket systems (EC000047)  
Feature Name  
Feature Value  
Height (EF000040)  
110 mm  
Width (EF000008)  
150 mm  
Material thickness (EF000386)  
1 mm  
Length (EF001438)  
3050 mm  
Working length (EF006318)  
3000 mm  
Useful cross section (EF005140)  
16100 mm<sup>2</sup>  
With cover (EF007965)  
No  
Side perforation (EF001122)  
Yes  
Bottom perforation (EF004545)  
Yes  
NATO-mounting holes (EF006059)  
No  
Model (EF000010)  
Integrated coupler  
Type of connector (EF000141)

Click in

Suitable for circuit integrity (EF007806)

No

Material (EF002169)

Steel

Surface protection (EF000139)

Hot dip galvanized

Weight (EF000167)

3.02 kg/m

Load test type acc...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / MKSM 115 FT with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.