

INDUSTRIAL COMPONENT DATA

MKSM 115 FT 6059175 OBO BETTERMANN Cable tray MKSM perforated with quick connector, 110x150x3050, Hot-dip ga..

Brand: OBO BETTERMANN | Manufacturer Part Number: MKSM 115 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	MKSM 115 FT
Catalog number	6059175
Category	Cable tray/wide span cable tray
Minimum order	3 m.
Document ID	EO-752E0EDD39
Generated	2026-08-02

Product Overview

Cable tray MKSM perforated with quick connector, 110x150x3050, Hot-dip galvanised, DIN EN ISO 1461, Steel, St MKSM MKSM 115 FT cable tray, perforated, with needle. 110x150x3050 Steel, St, Hot-dip galvanized, DIN EN ISO 1461 Cable tray MKS-Magic® 110 FT. Cable tray with integrated quick fastening system. The usable length of the cable tray is 3,000 mm. The cable tray has continuous side perforations of 7 x 20 mm for the installation of additional connection and mounting components. From a cable tray width of 200 mm with 30% hole surface, suitable for use under sprinkler systems according to VdS guideline 2092.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Rest sheet tray
--------------	---

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 7,2262 kg CO2e / 1 Meter

Colour zinc

Connector version Integrated connector

Dimension 110x150x3050

Dimension B 150 mm

Dimension L 30 mm

Dimension x 46 mm

Dimension y 112 mm

Height 110 mm

Length 3050 mm

Load test type according to IEC 61537 Type II
Magnetic shield insulation with cover 50 dB
Magnetic shield insulation without cover 20 dB
Maintain electrical functions no
Material Steel
Mounting perforation in base yes
NATO hole pattern no
Plate thickness 1 mm
Rustproof steel, pickled no
Side perforation yes
Support spacing 1.5 m 2 kN/m
Support spacing 2.0 m 1,5 kN/m
Support spacing 3.0 m 0,7 kN/m
Surface Hot-dip galvanised
Type of connector, cable support system Click fastening
Usable cross-section 161 cm²
Usable cross-section 16100 mm²
Usable length 3000 mm
Wide-span version no
Width 150 mm
With cover no
ETIM for 6059175 Cable tray, ladder and wire basket systems (EC000047)
Feature Name
Feature Value
Height (EF000040)
110 mm
Width (EF000008)
150 mm
Material thickness (EF000386)
1 mm
Length (EF001438)
3050 mm
Working length (EF006318)
3000 mm
Useful cross section (EF005140)
16100 mm²
With cover (EF007965)
No
Side perforation (EF001122)
Yes
Bottom perforation (EF004545)
Yes
NATO-mounting holes (EF006059)
No
Model (EF000010)
Integrated coupler
Type of connector (EF000141)

Click in

Suitable for circuit integrity (EF007806)

No

Material (EF002169)

Steel

Surface protection (EF000139)

Hot dip galvanized

Weight (EF000167)

3.02 kg/m

Load test type acc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / MKSM 115 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.