

INDUSTRIAL COMPONENT DATA

MKSM 140 FS 6059164 OBO BETTERMANN Cable tray MKSM perforated with quick connector, 110x400x3050, Strip-galv..

Brand: OBO BETTERMANN | Manufacturer Part Number: MKSM 140 FS



Manufacturer	OBO BETTERMANN
MPN / Reference	MKSM 140 FS
Catalog number	6059164
Category	Cable tray/wide span cable tray
Minimum order	3 m.
Document ID	EO-B31340BFA9
Generated	2026-07-31

Product Overview

Cable tray MKSM perforated with quick connector, 110x400x3050, Strip-galvanised, DIN EN 10147, Steel, St MKSM MKSM 140 FS cable tray, perforated, with needle. 110x400x3050 Steel, St, galvanized strip, DIN EN 10346 MKS-Magic® 110 FS cable tray. Cable tray with integrated quick fixing system. The usable length of the cable tray is 3,000 mm. La cable tray has a continuous side perforation of 7 x 20 mm for the installation of additional joining and mounting components. From a tray width of 200 mm, with 30% perforation percentage, suitable according to the VdS 2092 standard for use under fire sprinkler systems.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Rest sheet tray
--------------	---

Additional Product Information

MKSM 110 = medium-duty Magic cable tray system with a side height of 110 mm

ETIM for 6059164 Cable tray, ladder and wire basket systems (EC000047)

Feature Name

Feature Value

Height (EF000040)

110 mm

Width (EF000008)

400 mm

Material thickness (EF000386)

1 mm

Length (EF001438)

3050 mm

Working length (EF006318)

3000 mm

Useful cross section (EF005140)

43800 mm²

With cover (EF007965)

No

Side perforation (EF001122)

Yes

Bottom perforation (EF004545)

Yes

NATO-mounting holes (EF006059)

No

Model (EF000010)

Integrated coupler

Type of connector (EF000141)

Click in

Suitable for circuit integrity (EF007806)

No

Material (EF002169)

Steel

Surface protection (EF000139)

Pre-galvanised

Weight (EF000167)

3.69 kg/m

Load test type according to IEC 61537 (EF015362)

Type II

Possible support spacing (EF017261)

1.5 m

Safe working load according to IEC 61537 with support spacing 1.5 m (EF017264)

1800

Safe working load according to IEC 61537 with support spacing 2.0 m (EF017265)

1300

Safe working load according to IEC 61537 with support spacing 2.5 m (EF017266)

930

Safe working load according to IEC 61537 with support spacing 3.0 m (EF017267)

700

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / MKSM 140 FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.