

INDUSTRIAL COMPONENT DATA

MKSM 150 FT 6059183 OBO BETTERMANN Cable tray MKSM perforated with quick connector, 110x500x3050, Hot-dip ga..

Brand: OBO BETTERMANN | Manufacturer Part Number: MKSM 150 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	MKSM 150 FT
Catalog number	6059183
Category	Cable tray/wide span cable tray
Minimum order	3 m.
Document ID	EO-675E07471A
Generated	2026-08-02

Product Overview

Cable tray MKSM perforated with quick connector, 110x500x3050, Hot-dip galvanised, DIN EN ISO 1461, Steel, St MKSM MKSM 150 FT cable tray, perforated, with needle. 110x500x3050 Steel, St, Hot-dip galvanized, DIN EN ISO 1461 MKS-Magic® 110 FT. Cable Tray. Cable tray with integrated quick fixing system. The usable length of the cable tray is 3,000 mm. La cable tray has a continuous side perforation of 7 x 20 mm for the installation of additional joining and mounting components. From a tray width of 200 mm, with 30% perforation percentage, suitable according to the VdS 2092 standard for use under fire sprinkler systems.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Rest sheet tray
--------------	---

Additional Product Information

MKSM 110 = medium-duty Magic cable tray system with a side height of 110 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / MKSM 150 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.