


## INDUSTRIAL COMPONENT DATA

# MKSM 630 FS 6059006 OBO BETTERMANN Cable tray MKSM perforated with quick connector, 60x300x3050, Strip-galva..

Brand: OBO BETTERMANN | Manufacturer Part Number: MKSM 630 FS



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | OBO BETTERMANN                  |
| MPN / Reference | MKSM 630 FS                     |
| Catalog number  | 6059006                         |
| Category        | Cable tray/wide span cable tray |
| Minimum order   | 3 m.                            |
| Document ID     | EO-D03791D15E                   |
| Generated       | 2026-07-31                      |

## Product Overview

Cable tray MKSM perforated with quick connector, 60x300x3050, Strip-galvanised, DIN EN 10147, Steel, St Cable tray MKS-Magic® 60 FS. Cable tray with integrated quick fastening system. The usable length of the cable tray is 3,000 mm. The cable tray has continuous side perforations of 7 x 20 mm for the installation of additional connection and mounting components. From a cable tray width of 200 mm with 30% hole surface, suitable for use under sprinkler systems according to VdS guideline 2092.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path OBO BETTERMANN &gt; KTS cable support systems - OBO BETTERMANN &gt; Rest sheet tray

## Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 7,9825 kg CO2e / 1 Meter

Colour zinc

Connector version Integrated connector

Dimension 60x300x3050

Dimension B 300 mm

Dimension L 180 mm

Dimension x 196 mm

Dimension y 262 mm

Height 60 mm

Length 3050 mm

Load test type according to IEC 61537 Type II

Magnetic shield insulation with cover 50 dB  
Magnetic shield insulation without cover 20 dB  
Maintain electrical functions no  
Material Steel  
Mounting perforation in base yes  
NATO hole pattern no  
NEMA load class 8A  
Plate thickness 1 mm  
Rustproof steel, pickled no  
Side perforation yes  
Sprinkler system use yes  
Support spacing 1.5 m 1,5 kN/m  
Support spacing 2.0 m 1 kN/m  
Support spacing 2.5 m 0,7 kN/m  
Surface Strip galvanized  
Type of connector, cable support system Click fastening  
Usable cross-section 178 cm<sup>2</sup>  
Usable cross-section 17800 mm<sup>2</sup>  
Usable length 3000 mm  
Wide-span version no  
Width 300 mm  
With cover no

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / MKSM 630 FS with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.