

INDUSTRIAL COMPONENT DATA

MKSMU 110 FS 6059382 OBO BETTERMANN Cable tray

MKSMU unperf. with quick connector, 110x100x3050, Strip-galva..

Brand: OBO BETTERMANN | Manufacturer Part Number: MKSMU 110 FS



Manufacturer	OBO BETTERMANN
MPN / Reference	MKSMU 110 FS
Catalog number	6059382
Category	Cable tray/wide span cable tray
Minimum order	3 m.
Document ID	EO-3609709FB7
Generated	2026-08-02

Product Overview

Cable tray MKSMU unperf. with quick connector, 110x100x3050, Strip-galvanised, DIN EN 10147, Steel, St
MKSMU MKSMU 110 FS cable tray, s/drill, needle. 110x100x3050 Steel, St, galvanized in strip, DIN EN 10346
Cable tray MKS-Magic® 110, unperforated FS. Unperforated cable tray with integrated quick fastening system. The usable length of the cable tray is 3,000 mm.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Rest sheet tray
--------------	---

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 6,2071 kg CO2e / 1 Meter
Colour zinc
Connector version Integrated connector
Dimension 110x100x3050
Dimension B 100 mm
Height 110 mm
Length 3050 mm
Load test type according to IEC 61537 Type II
Maintain electrical functions no
Material Steel

Mounting perforation in base no
NATO hole pattern no
Plate thickness 1 mm
Rustproof steel, pickled no
Side perforation no
Support spacing 1.5 m 1,85 kN/m
Support spacing 2.0 m 1,3 kN/m
Support spacing 2.5 m 0,75 kN/m
Support spacing 3.0 m 0,6 kN/m
Surface Strip galvanized
Type of connector, cable support system Click fastening
Usable cross-section 10800 mm²
Usable cross-section 108 cm²
Usable length 3000 mm
Wide-span version no
Width 100 mm
With cover no
ETIM for 6059382 Cable tray, ladder and wire basket systems (EC000047)
Feature Name
Feature Value
Height (EF000040)
110 mm
Width (EF000008)
100 mm
Material thickness (EF000386)
1 mm
Length (EF001438)
3050 mm
Working length (EF006318)
3000 mm
Useful cross section (EF005140)
10800 mm²
With cover (EF007965)
No
Side perforation (EF001122)
No
Bottom perforation (EF004545)
No
NATO-mounting holes (EF006059)
No
Model (EF000010)
Integrated coupler
Type of connector (EF000141)
Click in
Suitable for circuit integrity (EF007806)
No
Material (EF002169)

Steel
Surface protection (EF000139)
Pre-galvanised
Weight (EF000167)
2.7 kg/m
Load test type according to IEC 61537 (EF015362)
Type II
Possible support spacing (EF017261)
1.5 m
Safe working load according to IEC 61537....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / MKSMU 110 FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.