

INDUSTRIAL COMPONENT DATA

MKSMU 640 FT 6059256 OBO BETTERMANN Cable tray MKSMU unperf. with quick connector, 60x400x3050, Hot-dip galv..

Brand: OBO BETTERMANN | Manufacturer Part Number: MKSMU 640 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	MKSMU 640 FT
Catalog number	6059256
Category	Cable tray/wide span cable tray
Minimum order	3 m.
Document ID	EO-91E7F4635C
Generated	2026-08-01

Product Overview

Cable tray MKSMU unperf. with quick connector, 60x400x3050, Hot-dip galvanised, DIN EN ISO 1461, Steel, St MKSMU MKSMU 640 FT cable tray, s/perforate, needle. 60x400x3050 Steel, St, Hot-dip galvanized, DIN EN ISO 1461 MKS-Magic® 60 non-perforated FT cable tray. Undrilled cable tray with integrated quick fixing system. The useful length of the cable tray is 3,000 mm.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Rest sheet tray

Additional Product Information

MKSMU 60 = Medium-duty Magic cable tray system, unperforated, with a side height of 60 mm

ETIM for 6059256 Cable tray, ladder and wire basket systems (EC000047)

Feature Name

Feature Value

Height (EF000040)

60 mm

Width (EF000008)

400 mm

Material thickness (EF000386)

1 mm

Length (EF001438)
3050 mm
Working length (EF006318)
3000 mm
Useful cross section (EF005140)
23800 mm²
With cover (EF007965)
No
Side perforation (EF001122)
No
Bottom perforation (EF004545)
No
NATO-mounting holes (EF006059)
No
Model (EF000010)
Integrated coupler
Type of connector (EF000141)
Click in
Suitable for circuit integrity (EF007806)
No
Material (EF002169)
Steel
Surface protection (EF000139)
Hot dip galvanized
Weight (EF000167)
4.69 kg/m
Load test type according to IEC 61537 (EF015362)
Type II
Possible support spacing (EF017261)
1.5 m
Safe working load according to IEC 61537 with support spacing 1.5 m (EF017264)
1500
Safe working load according to IEC 61537 with support spacing 2.0 m (EF017265)
1000
Safe working load according to IEC 61537 with support spacing 2.5 m (EF017266)
500

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / MKSMU 640 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.