

## INDUSTRIAL COMPONENT DATA

# MKSMU 820 FS 6059312 OBO BETTERMANN Cable tray

## MKSMU unperf. with quick connector, 85x200x3050, Strip-galvan..

Brand: OBO BETTERMANN | Manufacturer Part Number: MKSMU 820 FS



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | OBO BETTERMANN                  |
| MPN / Reference | MKSMU 820 FS                    |
| Catalog number  | 6059312                         |
| Category        | Cable tray/wide span cable tray |
| Minimum order   | 3 Pcs                           |
| Document ID     | EO-C6ABC2849D                   |
| Generated       | 2026-08-02                      |

### Product Overview

Cable tray MKSMU unperf. with quick connector, 85x200x3050, Strip-galvanised, DIN EN 10147, Steel, St  
Cable tray MKS-Magic® 85, unperforated FS. Unperforated cable tray with integrated quick fastening system. The usable length of the cable tray is 3,000 mm.

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                                                               |
|--------------|-------------------------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Rest sheet tray |
|--------------|-------------------------------------------------------------------------------|

### Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 7,1016 kg CO2e / 1 Meter

Colour zinc

Connector version Integrated connector

Dimension 85x200x3050

Dimension B 200 mm

Height 85 mm

Length 3050 mm

Load test type according to IEC 61537 Type II

Maintain electrical functions no

Material Steel

Mounting perforation in base no

NATO hole pattern no  
Plate thickness 1 mm  
Rustproof steel, pickled no  
Side perforation no  
Support spacing 1.5 m 1,75 kN/m  
Support spacing 1.75 m 1,4 kN/m  
Support spacing 2.0 m 1,1 kN/m  
Support spacing 2.5 m 0,5 kN/m  
Surface Strip galvanized  
Type of connector, cable support system Click fastening  
Usable cross-section 186 cm<sup>2</sup>  
Usable cross-section 18600 mm<sup>2</sup>  
Usable length 3000 mm  
Wide-span version no  
Width 200 mm  
With cover no

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / MKSMU 820 FS with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.